

Accessories

	Number of contacts	Contacts				Cat. no.	Ref. no.	Pack
		•3 •4	•1 •2	•7 •8	•5 •6			
 Mechanical interlock	Mechanical	-	-	-	-	BELA	104723	5
	Mechanical / electrical	2	0	2	-	BELA02	104724	5
 Mechanical latch blocks	Frontal mounted to the contactor							
					RL4RA..., RL4RD...	RMLF ♦ ⁽¹⁾	see bottom	20

(1) To complete the catalogue number, replace the symbol ♦ by the code corresponding to the voltage and frequency of the control circuit.

	D	G	HC	J	N	U	Y
50Hz	24, 32	42, 48		110, 115, 120, 127	220, 230, 240	380, 400, 415, 440, 480	500, 660/690
60HZ	24, 32	48, 60		110, 115, 120, 127	208, 220, 240, 277	380, 400, 415, 440, 480	600
DC	24, 32, 36	42, 48	60, 72	110, 120, 125	220, 230, 240, 250	440	

 Transient voltage supressor block	For use with:	Type	Control circ.	Ue	Cat. no.	Ref. no.	Pack
	Directly connected parallel to the coil terminals, allows simultaneous use with auxiliary contact blocks.						
	RL4RA...	R/C	AC	12V ... 48V	BSLR2G	104713	10
	RL4RA...	R/C	AC	50V ... 127V	BSLR2K	104714	10
	RL4RA...	R/C	AC	130V ... 250V	BSLR2R	104715	10
	RL4RD...	Diode	DC	12V ... 600V	BSLDZ	104719	10
	RL4RA..., RL4RD...	Varistor	AC / DC	24V ... 48V	BSLV3G	104720	10
	RL4RA..., RL4RD...	Varistor	AC / DC	50V ... 127V	BSLV3K	104721	10
	RL4RA..., RL4RD...	Varistor	AC / DC	130V ... 250V	BSLV3R	104722	10
	RL4RA..., RL4RD...	Varistor	AC / DC	277V ... 500V	BSLV3U	110836	10
Identification	For use with:				Cat. no.	Ref. no.	Pack
	RL4RA..., RL4RD...	Sheets of labels (10 sheets of 260 labels each)			EAT 260	100548	1
	RL4RA..., RL4RD...	Labelling plate base. Plug-in labeling plate bases (50 pieces in one pack)			SPR	100549	1
 Electronic timer module	For use with:	Control circuit	Function	Time	Cat. no.	Ref. no.	Pack
	Directly connected parallel to the coil terminals, allows simultaneous use with auxiliary contact blocks.						
	RL4...	24-250V AC/DC	Delayed ON	0,1 - 2 sec.	BETL02C	113602	5
	RL4...	24-250V AC/DC	Delayed ON	1,5 - 45 sec.	BETL45C	113603	5
	RL4...	24-250V AC/DC	Delayed OFF	0,1 - 2 sec.	BETL02D	113604	5
	RL4...	24-250V AC/DC	Delayed OFF	1,5 - 45 sec.	BETL45D	113605	5

For reference numbers, see chapter X, pg. X.7