Product data sheet

Specifications





socket, Harmony Electromechanical Relays, for RPM4 power relays, 16A screw clamp terminals, mixed contact

RPZF4

Product availability: Stock - Normally stocked in distribution facility

Price*: 8.91 USD

Main

Range Of Product	Harmony Electromechanical Relays
Device Short Name	RPZ
Product Or Component Type	Socket
Product Compatibility	Plug-in relay RPM 4 C/O
Contacts Type And Composition	4 C/O
[Ith] Conventional Free Air Thermal Current	16 A
[Ue] Rated Operational Voltage	< 250 V

Complementary

Shape Of Pin	Flat
Contact Terminal Arrangement	Mixed
Tightening Torque	< 1 N.m M3.5
Fixing Mode	By screw (panel) Clip-on (35 mm symmetrical DIN rail)
[Uimp] Rated Impulse Withstand Voltage	4 kV
Overvoltage Category	III
Pollution Degree	3
Sale Per Indivisible Quantity	10
Width	1.97 in (50 mm)
Net Weight	0.21 lb(US) (0.094 kg)

Environment

Connections - Terminals	 screw clamp terminals, flexible with cable end 1 x 0.51 x 2.5 mm² / AWG 20AWG 14 screw clamp terminals, solid without cable end 1 x 0.51 x 1.5 mm² / AWG 20AWG 16 screw clamp terminals, flexible with cable end 2 x 0.52 x 2.5 mm² / AWG 20AWG 14 screw clamp terminals, solid without cable end 2 x 0.52 x 1.5 mm² / AWG 20AWG 14
Ip Degree Of Protection	IP20 conforming to IEC 60529
Dielectric Strength	2500 V
Standards	IEC 61984

Price is "List Price" and may be subject to a trade discount - check with your local distributor or retailer for actual price.

Product Certifications	UL CSA
Marking	CE
Ambient Air Temperature For Storage	-40185 °F (-4085 °C)
Ambient Air Temperature For Operation	-40131 °F (-4055 °C)

Ordering and shipping details

Category	US10CP221128
Discount Schedule	0CP2
Gtin	3389119402316
Returnability	Yes
Country Of Origin	US

Packing Units

0	
Unit Type Of Package 1	PCE
Number Of Units In Package 1	1
Package 1 Height	1.18 in (2.994 cm)
Package 1 Width	1.98 in (5.03 cm)
Package 1 Length	3.30 in (8.379 cm)
Package 1 Weight	3.56 oz (101.0 g)
Unit Type Of Package 2	BB1
Number Of Units In Package 2	10
Package 2 Height	2.60 in (6.6 cm)
Package 2 Width	3.46 in (8.8 cm)
Package 2 Length	9.88 in (25.1 cm)
Package 2 Weight	2.23 lb(US) (1.01 kg)
Unit Type Of Package 3	S03
Number Of Units In Package 3	110
Package 3 Height	11.81 in (30.0 cm)
Package 3 Width	11.81 in (30.0 cm)
Package 3 Length	15.75 in (40.0 cm)
Package 3 Weight	25.68 lb(US) (11.65 kg)

Contractual warranty

Warranty

18 months

Sustainability Screen Premium

Green PremiumTM label is Schneider Electric's commitment to delivering products with best-inclass environmental performance. Green Premium promises compliance with the latest regulations, transparency on environmental impacts, as well as circular and low-CO₂ products.

Guide to assessing product sustainability is a white paper that clarifies global eco-label standards and how to interpret environmental declarations.

Learn more about Green Premium >

Guide to assess a product's sustainability >



Transparency RoHS/REACh

Well-being performance

Reach Free Of Svhc
 Toxic Heavy Metal Free
 Mercury Free
 Rohs Exemption Information Yes


Certifications & Standards

Reach Regulation	REACh Declaration
Eu Rohs Directive	Pro-active compliance (Product out of EU RoHS legal scope) EU RoHS Declaration
China Rohs Regulation	China RoHS declaration
Environmental Disclosure	Product Environmental Profile
Weee	The product must be disposed on European Union markets following specific waste collection and never end up in rubbish bins.
Circularity Profile	No need of specific recycling operations
California Proposition 65	WARNING: This product can expose you to chemicals including: Nickel compounds, which is known to the State of California to cause cancer, and Di-isodecyl phthalate (DIDP), which is known to the State of California to cause birth defects or other reproductive harm. For more information go to www.P65Warnings.ca.gov

Product data sheet

Dimensions Drawings

Dimensions




(1) Relays(2) Protection module(3) Maintaining clamp

Product data sheet

Connections and Schema

Wiring Diagram



Symbols shown in blue correspond to Nema marking.