Specifications





interface plug-in relay, Harmony electromechanical relays, 16A, 1CO, 220V AC

RSB1A160M7

Product availability: Non-Stock - Not normally stocked in distribution facility

Price*: 5.12 USD

Main

Range Of Product	Harmony Electromechanical Relays
Series Name	Interface relay
Product Or Component Type	Plug-in relay
Device Short Name	RSB
Contacts Type And Composition	1 C/O
Contact Operation	Standard
[Uc] Control Circuit Voltage	220 V AC 50/60 Hz
[Ithe] Conventional Enclosed Thermal Current	16 A -40104 °F (-4040 °C)
Status Led	Without
Control Type	Without push-button

Complementary

· · · · · · · · · · · · · · · · · · ·	
Shape Of Pin	Flat (PCB type)
Average Coil Resistance	33000 Ohm AC 20 °C +/- 10 %
[Ue] Rated Operational Voltage	176330 V AC 50/60 Hz
[Ui] Rated Insulation Voltage	400 V IEC 60947
[Uimp] Rated Impulse Withstand Voltage	3.6 kV IEC 61000-4-5
Contacts Material	Silver alloy (AgNi)
[le] Rated Operational Current	16 A AC-1/DC-1) NO IEC 8 A AC-1/DC-1) NC IEC
Minimum Switching Current	10 mA
Maximum Switching Voltage	300 V DC IEC
Minimum Switching Voltage	12 V
Maximum Switching Capacity	4000 VA/448 W
Resistive Rated Load	16 A 250 V AC 16 A 28 V DC
Minimum Switching Capacity	120 mW 10 mA, 12 V
Operating Rate	<= 600 cycles/hour under load <= 18000 cycles/hour no-load
Mechanical Durability	1000000 cycles

Price is "List Price" and may be subject to a trade discount - check with your local distributor or retailer for actual price.

Electrical Durability	100000 cycles, 16 A at 250 V, AC-1 NO 100000 cycles, 8 A at 250 V, AC-1 NC	
Operating Time	20 ms operating 20 ms reset	
Average Coil Consumption	0.75 VA AC	
Drop-Out Voltage Threshold	>= 0.15 Uc AC	
Safety Reliability Data	B10d = 100000	
Protection Category	RT I	
Test Levels	Level A group mounting	
Operating Position	Any position	
Net Weight	0.03 lb(US) (0.014 kg)	
Sale Per Indivisible Quantity	10	
Device Presentation	Complete product	

Environment

Dielectric Strength	1000 V AC between contacts 2500 V AC between poles 5000 V AC between coil and contact	
Standards	CSA C22.2 No 14 IEC 61810-1 UL 508	
Product Certifications	EAC UL CSA	
Ambient Air Temperature For Storage	-40185 °F (-4085 °C)	
Vibration Resistance	+/- 1 mm 1055 Hz)IEC 60068-2-6	
Ip Degree Of Protection	IP40 conforming to IEC 60529	
Shock Resistance	10 gn 11 ms) not operating IEC 60068-2-27 5 gn 11 ms) in operation IEC 60068-2-27	
Ambient Air Temperature For Operation	-40158 °F (-4070 °C) AC)	

Ordering and shipping details

Category	US10CP221127	
Discount Schedule	0CP2	
Gtin	3389110260038	
Returnability	No	
Country Of Origin	AT	

Packing Units

Unit Type Of Package 1	PCE
Number Of Units In Package 1	1
Package 1 Height	0.67 in (1.7 cm)
Package 1 Width	0.98 in (2.5 cm)
Package 1 Length	1.22 in (3.1 cm)
Package 1 Weight	0.53 oz (15.0 g)
Unit Type Of Package 2	BB1

Number Of Units In Package 2	10	
Package 2 Height	0.71 in (1.8 cm)	
Package 2 Width	1.02 in (2.6 cm)	
Package 2 Length	12.20 in (31.0 cm)	
Package 2 Weight	5.61 oz (159.0 g)	
Unit Type Of Package 3	S01	
Number Of Units In Package 3	350	
Package 3 Height	5.91 in (15.0 cm)	
Package 3 Width	5.91 in (15.0 cm)	
Package 3 Length	15.75 in (40.0 cm)	
Package 3 Weight	11.45 lb(US) (5.195 kg)	

Contractual warranty

Warranty

18 months

Sustainability Screen Premium

Green PremiumTM label is Schneider Electric's commitment to delivering products with best-inclass environmental performance. Green Premium promises compliance with the latest regulations, transparency on environmental impacts, as well as circular and low-CO₂ products.

Guide to assessing product sustainability is a white paper that clarifies global eco-label standards and how to interpret environmental declarations.

Learn more about Green Premium >

Guide to assess a product's sustainability >



Transparency RoHS/REACh

Well-being performance


Toxic Heavy Metal Free
Mercury Free
Rohs Exemption Information Yes

Certifications & Standards

Reach Regulation	REACh Declaration
Eu Rohs Directive	Pro-active compliance (Product out of EU RoHS legal scope) EU RoHS Declaration
China Rohs Regulation	China RoHS declaration
Environmental Disclosure	Product Environmental Profile
Weee	The product must be disposed on European Union markets following specific waste collection and never end up in rubbish bins.
Circularity Profile	No need of specific recycling operations
California Proposition 65	WARNING: This product can expose you to chemicals including: Nickel compounds, which is known to the State of California to cause cancer, and Di-isodecyl phthalate (DIDP), which is known to the State of California to cause birth defects or other reproductive harm. For more information go to www.P65Warnings.ca.gov


Dimensions Drawings

Dimensions



Connections and Schema

Wiring Diagram




(1) Terminals 11 and 21,14 and 24,12 and 22 must be linked for this references

NOTE: For DC input, A1 have to be +, otherwise it would short circuit from protection module


Performance Curves

Electrical Durability of Contacts

Durability (inductive load) = durability (resistive load) x reduction coefficient. Resistive AC load




X Switching capacity (kVA) Y Durability (Number of operating cycles) Reduction coefficient for inductive AC load (depending on power factor cos φ)



Y Reduction coefficient (A)

Maximum switching capacity on resistive DC load



X Voltage DCY Current DCNote : These are typical curves, actual durability depends on load, environment, duty cycle, etc.