Product datasheet





Harmony, Universal plug-in relay, 10 A, 2 CO, with lockable test button, flat (faston) terminals, 120 **VAC**

RUMF21F7



! Discontinued on: 30 Jun 2023



Main

Range of product	Harmony Electromechanical Relays	
Series name	Universal	
Product or component type	Plug-in relay	
Device short name	RUM	
Contacts type and composition	2 C/O	
[Uc] control circuit voltage	120 V AC 50/60 Hz	
[Ithe] conventional enclosed thermal current	10 A at -4055 °C	
Status LED	Without	
Control type	Lockable test button	
Utilisation coefficient	20 %	

Complementary

Shape of pin	Flat
[Ui] rated insulation voltage	250 V conforming to IEC
	300 V conforming to CSA
	300 V conforming to UL
[Uimp] rated impulse withstand voltage	4 kV (1.2/50 μs)
Contacts material	AgNi
[le] rated operational current	10 A at 277 V AC conforming to UL
	10 A at 30 V DC conforming to UL
	10 A at 30 V DC conforming to CSA
	5 A at 250 V AC (NC) conforming to IEC
	5 A at 28 V DC (NC) conforming to IEC
	10 A at 250 V AC (NO) conforming to IEC
	10 A at 28 V DC (NO) conforming to IEC
	10 A at 277 V AC conforming to CSA
Maximum switching voltage	250 V conforming to IEC
Resistive rated load	10 A at 250 V AC
	10 A at 28 V DC
Maximum switching capacity	2500 VA/280 W
Minimum switching capacity	170 mW at 10 mA, 17 V
Operating rate	<= 18000 cycles/hour no-load
	<= 1200 cycles/hour under load
Mechanical durability	5000000 cycles
Electrical durability	100000 cycles for resistive load

Life Is On Schneider 16 Jul 2024

Average coil consumption in VA	3 at 60 Hz	
Drop-out voltage threshold	>= 0.15 Uc AC	
Operate time	20 ms at nominal voltage	
Release time	20 ms at nominal voltage	
Average coil resistance	1700 Ohm at 20 °C +/- 15 %	
Rated operational voltage limits	96132 V AC	
Protection category	RTI	
Test levels	Level A group mounting	
Safety reliability data	B10d = 100000	
Operating position	Any position	
Net weight	0.086 kg	
device presentation	Complete product	

Environment

Dielectric strength	1500 V AC between contacts with micro disconnection	
	2500 V AC between coil and contact with reinforced 2000 V AC between poles with basic	
Product certifications	UL	
	EAC	
	CSA	
Standards	UL 508	
	CSA C22.2 No 14	
	EN/IEC 61810-1	
ambient air temperature for storage	-4085 °C	
Ambient air temperature for operation	-4055 °C	
Vibration resistance	3 gn, amplitude = +/- 1 mm (f = 10150 Hz)5 cycles in operation	
	4 gn, amplitude = +/- 1 mm (f = 10150 Hz)5 cycles not operating	
IP degree of protection	IP40	
Shock resistance	10 gn (duration = 11 ms) for in operation conforming to EN/IEC 60068-2-27 10 gn (duration = 11 ms) for not operating conforming to EN/IEC 60068-2-27	
Pollution degree	3	

Packing Units

Unit Type of Package 1	PCE
Number of Units in Package 1	1
Package 1 Height	3.7 cm
Package 1 Width	3.8 cm
Package 1 Length	7.2 cm
Package 1 Weight	92.0 g
Unit Type of Package 2	BB1
Number of Units in Package 2	10
Package 2 Height	13.2 cm
Package 2 Width	20.0 cm
Package 2 Length	38.0 cm
Package 2 Weight	880.0 g

Unit Type of Package 3	S02
Number of Units in Package 3	60
Package 3 Height	15.0 cm
Package 3 Width	30.0 cm
Package 3 Length	40.0 cm
Package 3 Weight	5.9 kg

Sustainability Green Premium

Green PremiumTM **label** is Schneider Electric's commitment to delivering products with best-inclass environmental performance. Green Premium promises compliance with the latest regulations, transparency on environmental impacts, as well as circular and low-CO₂ products.

Guide to assessing product sustainability is a white paper that clarifies global eco-label standards and how to interpret environmental declarations.

Learn more about Green Premium >

Guide to assess a product's sustainability >





Transparency RoHS/REACh

Well-being performance



Reach Free Of Svhc



Rohs Exemption Information

Yes

Certifications & Standards

Reach Regulation	REACh Declaration
Eu Rohs Directive	Pro-active compliance (Product out of EU RoHS legal scope) EU RoHS Declaration
China Rohs Regulation	China RoHS declaration
Environmental Disclosure	Product Environmental Profile
Circularity Profile	No need of specific recycling operations