Specifications





## universal plug-in relay - Harmony RUM - 2 C/O - 230 V AC - 10 A with LED

RUMF23P7

() Discontinued on: Jan 29, 2021

(!) Discontinued

### Main

Range of Product	Harmony Relay
Series name	Universal
Product or Component Type	Plug-in relay
Device short name	RUM
Contacts type and composition	2 C/O
[Uc] control circuit voltage	230 V AC 50/60 Hz
[Ithe] conventional enclosed thermal current	10 A -40.00000000131.000000000 °F (-4055 °C)
Status LED	With
Control Type	Without lockable test button
Utilisation coefficient	20 %

## Complementary

Shape of pin	Flat
[Ui] rated insulation voltage	250 V IEC
	300 V CSA
	300 V UL
[Uimp] rated impulse withstand voltage	4 kV 1.2/50 μs)
Contacts material	AgNi
[le] rated operational current	10 A at 277 V AC conforming to UL
	10 A at 30 V DC conforming to UL
	10 A at 30 V DC conforming to CSA
	5 A at 250 V AC (NC) conforming to IEC
	5 A at 28 V DC (NC) conforming to IEC
	10 A at 250 V AC (NO) conforming to IEC
	10 A at 28 V DC (NO) conforming to IEC
	10 A at 277 V AC conforming to CSA
Maximum switching voltage	250 V IEC
Resistive rated load	10 A 250 V AC
	10 A 28 V DC
Maximum switching capacity	2500 VA/280 W
Minimum switching capacity	170 mW 10 mA, 17 V
Operating rate	<= 18000 cycles/hour no-load
	<= 1200 cycles/hour under load
Mechanical durability	5000000 cycles
Electrical durability	100000 cycles resistive

Price is "List Price" and may be subject to a trade discount - check with your local distributor or retailer for actual price.

Average coil consumption in VA	3 60 Hz	
Drop-out voltage threshold	>= 0.15 Uc AC	
Operate time	20 ms at nominal voltage	
Release time	20 ms at nominal voltage	
Average coil resistance	6800 Ohm 20 °C +/- 15 %	
Rated operational voltage limits	184253 V AC	
Protection category	RTI	
Test levels	Level A group mounting	
Safety reliability data	B10d = 100000	
Operating position	Any position	
Net Weight	0.190 lb(US) (0.086 kg)	
device presentation	Complete product	

## Environment

1500 V AC between contacts with micro disconnection 2500 V AC between coil and contact with reinforced
2000 V AC between poles with basic
EAC
CSA
UL
CSA C22.2 No 14
UL 508
EN/IEC 61810-1
-40.000000000185.0000000000 °F (-4085 °C)
-40.000000000131.0000000000 °F (-4055 °C)
3 gn +/- 1 mm 10…150 Hz)5 cycles in operation
4 gn +/- 1 mm 10150 Hz)5 cycles not operating
IP40
10 gn 11 ms) in operation EN/IEC 60068-2-27
10 gn 11 ms) not operating EN/IEC 60068-2-27
3

# Ordering and shipping details

Category	21127-ZELIO ICE CUBE RELAYS	
Discount Schedule	CP2	
GTIN	00785901989530	
Returnability	No	
Country of origin	CN	

# **Packing Units**

<u> </u>	
Unit Type of Package 1	PCE
Number of Units in Package 1	1

# Sustainability Screen Premium

**Green Premium<sup>TM</sup> label** is Schneider Electric's commitment to delivering products with best-inclass environmental performance. Green Premium promises compliance with the latest regulations, transparency on environmental impacts, as well as circular and low-CO<sub>2</sub> products.

**Guide to assessing product sustainability** is a white paper that clarifies global eco-label standards and how to interpret environmental declarations.

Learn more about Green Premium >

Guide to assess a product's sustainability >



Transparency RoHS/REACh

## Well-being performance

Reach Free Of Svhc


Rohs Exemption Information Yes

## **Certifications & Standards**

Reach Regulation	REACh Declaration
Eu Rohs Directive	Pro-active compliance (Product out of EU RoHS legal scope) EU RoHS Declaration
China Rohs Regulation	China RoHS declaration
Environmental Disclosure	Product Environmental Profile
Circularity Profile	No need of specific recycling operations
California Proposition 65	WARNING: This product can expose you to chemicals including: Nickel compounds, which is known to the State of California to cause cancer, and Di-isodecyl phthalate (DIDP), which is known to the State of California to cause birth defects or other reproductive harm. For more information go to www.P65Warnings.ca.gov

### **Dimensions Drawings**


### Dimensions




4

Connections and Schema

### Wiring Diagram



### Wiring Diagram




Symbols shown in blue correspond to Nema marking.

6

#### Performance Curves

#### **Electrical Durability of Contacts**


Durability (inductive load) = durability (resistive load) x reduction coefficient. Resistive AC load



X Switching capacity (kVA)

Y Durability (Number of operating cycles)

Reduction coefficient for inductive AC load (depending on power factor  $\cos\varphi)$ 



Y Reduction coefficient (A)

Maximum switching capacity on resistive DC load

