Product data sheet





interface plug in relay, Harmony Electromechanical Relays, 10A, 1CO, lockable test but to n, 110V DC

RXG11JD

! Discontinued on: Oct 9, 2023

Product availability: Non-Stock - Not normally stocked in distribution facility

Main

Range Of Product	Harmony Electromechanical Relays	
Series Name	Interface relay	
Product Or Component Type	Plug-in relay	
Device Short Name	RXG	
Contacts Type And Composition	1 C/O	
[Ithe] Conventional Enclosed Thermal Current	10 A -40131 °F (-4055 °C)	
Local Signalling	Flag	

Complementary

Status Led	Without	
[le] Rated Operational Current	10 A 30 V DC) UL 10 A 30 V DC) IEC 10 A 250 V AC) IEC 10 A 250 V AC) UL	
Electrical Durability	100000 cycles NO resistive at 55 °C 100000 cycles NC resistive at 55 °C	
Coil Resistance	270 Ohm +/- 10 %	
Shock Resistance	20 gn in operation 100 gn not in operation	
Mounting Position	Any position	
[Uc] Control Circuit Voltage	12 V DC	
Colour Of Cover	Standard	
Drop-Out Voltage Threshold	>= 0.1 Uc DC	
Load Current	10 A 250 V AC	
Minimum Switching Capacity	500 mW at 100 mA, 5 V DC	
Maximum Switching Capacity	2500 VA	
Control Type	Lockable test button	
Torque Value	7.08 lbf.in (0.8 N.m)	
Contact Resistance	100 mOhm	
Insulation Resistance	1000 MOhm at 500 V DC	
Electrical Insulation Class	Class F	

Price is "List Price" and may be subject to a trade discount - check with your local distributor or retailer for actual price.

g Voltage 250 V AC 30 V DC	

Environment

Standards	IEC 61810-1 CSA C22.2 No 14 UL 508	
Product Certifications	CSA CE EAC UL DNV-GL	
Ambient Air Temperature For Storage	-40185 °F (-4085 °C)	
Ambient Air Temperature For Operation	-40158 °F (-4070 °C)	
Ip Degree Of Protection	IP40	
Relative Humidity	1085 %	
Vibration Resistance	3 gn +/- 0.75 mm 10150 Hz)in operation 5 gn +/- 0.75 mm 10150 Hz)not in operation	

Ordering and shipping details

Category	US10CP221127	
Discount Schedule	0CP2	
Gtin	3606480688614	
Returnability	No	
Country Of Origin	CN	

Packing Units

Unit Type Of Package 1 PCE

Number Of Units In Package 1	1	
Package 1 Height	1.36 in (3.45 cm)	
Package 1 Width	3.64 in (9.25 cm)	
Package 1 Length	3.39 in (8.6 cm)	
Package 1 Weight	7.97 oz (226 g)	

Sustainability Screen Premium

Green PremiumTM **label** is Schneider Electric's commitment to delivering products with best-inclass environmental performance. Green Premium promises compliance with the latest regulations, transparency on environmental impacts, as well as circular and low-CO₂ products.

Guide to assessing product sustainability is a white paper that clarifies global eco-label standards and how to interpret environmental declarations.

Learn more about Green Premium >

Guide to assess a product's sustainability >





Transparency RoHS/REACh

Well-being performance


Ø	Reach Free Of Svhc	
Ø	Toxic Heavy Metal Free	
	Mercury Free	
9	Rohs Exemption Information	Yes


Certifications & Standards


Reach Regulation	REACh Declaration
Eu Rohs Directive	Pro-active compliance (Product out of EU RoHS legal scope) EU RoHS Declaration
China Rohs Regulation	China RoHS declaration
Environmental Disclosure	Product Environmental Profile
Circularity Profile	No need of specific recycling operations
California Proposition 65	WARNING: This product can expose you to chemicals including: Nickel compounds, which is known to the State of California to cause cancer, and Di-isodecyl phthalate (DIDP), which is known to the State of California to cause birth defects or other reproductive harm. For more information go to www.P65Warnings.ca.gov

Dimensions Drawings

Dimensions








Product data sheet

RXG11JD

Connections and Schema


Wiring Diagram



Performance Curves

Performance Curves

Maximum Switching Capacity



X : Switching voltage (V)

Y: Switching current (A)

(1) AC Resistive Load


(2) AC Inductive Load cos(Ø)=0.4

(3) DC Resistive Load

(4) DC Inductive Load (L/R=7ms)

Life Expectancy

Resistive Load




X: Contact Current (A)

Y: Operating Cycle Number

Life Expectancy

Inductive Load



X: Contact Current (A)

Y: Operating Cycle Number


Product data sheet

RXG11JD

NOTE: These are typical curves, actual durability depends on load, environment, duty cycle, etc.

Coil Operating Range

DC Coil Operating Range VS Ambient Temperature



 ${\bf X}$: Ambient temperature (°C)

Y: Coil voltage (U/Uc)

(1) Permitted operating range area