Product data sheet

Specifications





interface plug in relay, Harmony Electromechanical Relays, 5A, 2CO, lockable test but to n, 48V AC

RXG21E7

Product availability: Non-Stock - Not normally stocked in distribution facility

Price*: 11.34 USD

Main

Range of Product	Harmony Electromechanical Relays	
Series name	Interface relay	
Product or Component Type	Plug-in relay	
Device short name	RXG	
Contacts type and composition	n 2 C/O	
[Ithe] conventional enclosed thermal current	5 A -40131 °F (-4055 °C)	
local signalling	Flag	

Complementary

Status LED	Without	
[le] rated operational current	5 A 30 V DC) UL 5 A 30 V DC) IEC 5 A 250 V AC) IEC 5 A 250 V AC) UL	
Electrical durability	100000 cycles NO resistive at 55 °C 100000 cycles NC resistive at 55 °C	
Coil resistance	1100 Ohm +/- 10 %	
Shock resistance	20 gn in operation 100 gn not in operation	
mounting position	Any position	
Average consumption in VA	0.82 VA 60 Hz	
Control circuit voltage limits	0.81.1 Uc AC	
[Uc] control circuit voltage	48 V AC 50/60 Hz	
Colour of cover	Standard	
Drop-out voltage threshold	>= 0.3 Uc AC	
Load current	5 A 250 V AC	
Minimum switching capacity	50 mW at 10 mA, 5 V DC	
Maximum switching capacity	1250 VA	
Control Type	Lockable test button	
Torque Value	7.08 lbf.in (0.8 N.m)	
Contact resistance	100 mOhm	

Price is "List Price" and may be subject to a trade discount – check with your local distributor or retailer for actual price.

Insulation resistance	1000 MOhm at 500 V DC	
Electrical Insulation Class	Class F	
Mechanical durability	10000000 cycles	
Safety reliability data	B10d = 100000	
Operating time	20 ms	
Reset time	20 ms	
Overvoltage category	rvoltage category III	
Maximum switching voltage	250 V AC 30 V DC	
Protection category	tegory RT I	
Operating rate	<= 1800 cycles/hour under load <= 18000 cycles/hour no-load	
Pollution degree	2	
Utilisation coefficient	20 %	
[Ui] rated insulation voltage	250 V IEC 300 V CSA 300 V UL	
Dielectric strength	1000 V AC between contacts with micro disconnection 5000 V AC between coil and contact with reinforced insulation 3000 V AC between poles with basic insulation	
Test levels	Level A group mounting	
device presentation	Complete product	
Contacts material	Silver alloy (AgSnO2In2O3)	
Net Weight	0.04 lb(US) (0.02 kg)	

Environment

Standards	UL 508 IEC 61810-1 CSA C22.2 No 14
Product Certifications	CSA UL EAC CE DNV-GL
Ambient Air Temperature for Storage	-40185 °F (-4085 °C)
Ambient Air Temperature for Operation	-40158 °F (-4070 °C)
IP Degree of Protection	IP40
Relative humidity	1085 %
Vibration resistance	3 gn +/- 0.75 mm 10150 Hz)in operation 5 gn +/- 0.75 mm 10150 Hz)not in operation

Ordering and shipping details

Category	US10CP221127	
Discount Schedule	0CP2	
GTIN	3606480689000	
Returnability	No	
Country of origin	CN	

Packing Units

Unit Type of Package 1	PCE	
Number of Units in Package 1	1	
Package 1 Height	1.36 in (3.45 cm)	
Package 1 Width	3.64 in (9.25 cm)	
Package 1 Length	3.4 in (8.6 cm)	
Package 1 Weight	7.7 oz (219 g)	
Unit Type of Package 2	BB1	
Number of Units in Package 2	10	
Package 2 Height	1.4 in (3.5 cm)	
Package 2 Width	3.2 in (8.2 cm)	
Package 2 Length	3.6 in (9.1 cm)	
Package 2 Weight	7.8 oz (221 g)	
Unit Type of Package 3	S01	
Number of Units in Package 3	200	
Package 3 Height	5.9 in (15 cm)	
Package 3 Width	5.9 in (15 cm)	
Package 3 Length	15.7 in (40 cm)	
Package 3 Weight	10.21 lb(US) (4.63 kg)	

Sustainability Screen Premium

Green PremiumTM **label** is Schneider Electric's commitment to delivering products with best-inclass environmental performance. Green Premium promises compliance with the latest regulations, transparency on environmental impacts, as well as circular and low-CO₂ products.

Guide to assessing product sustainability is a white paper that clarifies global eco-label standards and how to interpret environmental declarations.

Learn more about Green Premium >

Guide to assess a product's sustainability >





Transparency RoHS/REACh

Well-being performance

Ø	Reach Free Of Svhc	
Ø	Toxic Heavy Metal Free	
	Mercury Free	
9	Rohs Exemption Information	Yes

Certifications & Standards

Reach Regulation	REACh Declaration
Eu Rohs Directive	Pro-active compliance (Product out of EU RoHS legal scope) EU RoHS Declaration
China Rohs Regulation	China RoHS declaration
Environmental Disclosure	Product Environmental Profile
Circularity Profile	No need of specific recycling operations
California Proposition 65	WARNING: This product can expose you to chemicals including: Nickel compounds, which is known to the State of California to cause cancer, and Di-isodecyl phthalate (DIDP), which is known to the State of California to cause birth defects or other reproductive harm. For more information go to www.P65Warnings.ca.gov