# **Product datasheet**





## Miniature plug in relay, Harmony, 3A, 4CO, lockable test button, 24V AC

RXM4GB1B7

! Discontinued on: 10 Jul 2021

! Discontinued

### Main

Range Of Product	Harmony Electromechanical Relays	
Series Name	Miniature	
Product Or Component Type	Plug-in relay	
Device Short Name	RXM	
Contacts Type And Composition	4 C/O	
[Uc] Control Circuit Voltage	24 V AC 50/60 Hz	
[Ithe] Conventional Enclosed Thermal Current	3 A at -4055 °C	
Status Led	Without	
Control Type	Lockable test button	
Utilisation Coefficient	20 %	

## Complementary

Shape Of Pin	Flat
[Ui] Rated Insulation Voltage	250 V conforming to IEC
	300 V conforming to CSA
	300 V conforming to UL
[Uimp] Rated Impulse Withstand Voltage	2.5 kV during 1.2/50 μs
Contacts Material	Gold plated bifurcated silver
[le] Rated Operational Current	2 A at 28 V (DC) NO conforming to IEC
	2 A at 250 V (AC) NO conforming to IEC
	1 A at 28 V (DC) NC conforming to IEC
	1 A at 250 V (AC) NC conforming to IEC
	3 A at 28 V (DC) conforming to UL
	3 A at 277 V (AC) conforming to UL
Maximum Switching Voltage	250 V conforming to IEC
Resistive Rated Load	3 A at 250 V AC
	3 A at 28 V DC
Maximum Switching Capacity	750 VA/84 W
Minimum Switching Capacity	15 mW at 3 mA, 5 V
Operating Rate	<= 1200 cycles/hour under load
	<= 18000 cycles/hour no-load
Mechanical Durability	10000000 cycles
Electrical Durability	100000 cycles for resistive load depending on mounting position and working environment
Average Coil Consumption In Va	1.2 at 60 Hz

Average Consumption	1.2 VA at 60 Hz	
Drop-Out Voltage Threshold	>= 0.15 Uc	
Operate Time	20 ms	
Release Time	20 ms	
Average Coil Resistance	180 Ohm at 20 °C +/- 15 %	
Rated Operational Voltage Limits	19.226.4 V AC	
Protection Category	RTI	
Test Levels	Level A group mounting	
Operating Position	Any position	
Net Weight	0.037 kg	
Device Presentation	Complete product	

## **Environment**

Dielectric Strength	1300 V AC between contacts with micro disconnection	
Dictional Guiding an	2000 V AC between coil and contact	
	2000 V AC between poles	
Product Certifications	UL	
	Lloyd's	
	CE	
	CSA	
	GOST	
	IECEE CB Scheme	
Standards	IEC 61810-1	
	UL 508	
	CSA C22.2 No 14	
Ambient Air Temperature For Storage	-4085 °C	
Ambient Air Temperature For Operation	-4055 °C	
Vibration Resistance	3 gn, amplitude = +/- 1 mm (f = 10150 Hz)5 cycles in operation 5 gn, amplitude = +/- 1 mm (f = 10150 Hz)5 cycles not operating	
Ip Degree Of Protection	IP40 conforming to IEC 60529	
Shock Resistance	10 gn for in operation	
	30 gn for not operating	
Pollution Degree	2	

# **Packing Units**

•	
Unit Type Of Package 1	PCE
Number Of Units In Package 1	1
Package 1 Height	2.000 cm
Package 1 Width	2.800 cm
Package 1 Length	4.800 cm
Package 1 Weight	35.000 g
Unit Type Of Package 2	BB1
Number Of Units In Package 2	10
Package 2 Height	3.200 cm
Package 2 Width	10.500 cm
Package 2 Length	12.500 cm

Package 2 Weight	381.000 g
	301.000 g
Unit Type Of Package 3	S01
Number Of Units In Package 3	120
Package 3 Height	15.000 cm
Package 3 Width	15.000 cm
Package 3 Length	40.000 cm
Package 3 Weight	4.810 kg

## **Contractual warranty**

Warranty 18 months

## Sustainability Green Premium

**Green Premium**<sup>TM</sup> **label** is Schneider Electric's commitment to delivering products with best-inclass environmental performance. Green Premium promises compliance with the latest regulations, transparency on environmental impacts, as well as circular and low-CO<sub>2</sub> products.

**Guide to assessing product sustainability** is a white paper that clarifies global eco-label standards and how to interpret environmental declarations.

Learn more about Green Premium >

Guide to assess a product's sustainability >





Transparency RoHS/REACh

## Well-being performance



Reach Free Of Svhc



Rohs Exemption Information

Yes


## **Certifications & Standards**

Reach Regulation	REACh Declaration
Eu Rohs Directive	Pro-active compliance (Product out of EU RoHS legal scope)  EU RoHS Declaration
China Rohs Regulation	China RoHS declaration
Environmental Disclosure	Product Environmental Profile
Weee	The product must be disposed on European Union markets following specific waste collection and never end up in rubbish bins
Circularity Profile	End of Life Information


17 Jun 2024

## **Dimensions Drawings**

## **Dimensions**



#### Pin Side View




### RXM4GB1B7

Connections and Schema

## Wiring Diagram





Symbols shown in blue correspond to Nema marking.


### **Product datasheet**

## RXM4GB1B7

#### Performance Curves

#### **Electrical Durability of Contacts**

**Durability (inductive load) = durability (resistive load) x reduction coefficient.**Resistive AC load



X Switching capacity (kVA)

Y Durability (Number of operating cycles)


A RXM2AB\*\*\*

B RXM3AB•••

C RXM4AB•••


**D** RXM4GB•••

Reduction coefficient for inductive AC load (depending on power factor cos φ)



#### Y Reduction coefficient (A)

Maximum switching capacity on resistive DC load



**X** Voltage DC

Y Current DC

A RXM2AB•••

B RXM3AB•••
C RXM4AB•••

D RXM4GB•••

Note: These are typical curves, actual durability depends on load, environment, duty cycle, etc.