# **Product data sheet**

Specification





# Miniature Plug-in relay - Harmony RXM 4 C/O 48 V DC 3 A with LED

RXM4GB3ED

! Discontinued on: Jan 29, 2021

① Discontinued

#### Main

*******		
Range of Product	Harmony Relay	
Series name	Miniature	
Product or Component Type	Plug-in relay	
Device short name	RXM	
Contacts type and composition	4 C/O	
[Uc] control circuit voltage	48 V DC	
[Ithe] conventional enclosed thermal current	3 A -40131 °F (-4055 °C)	
Status LED	With	
Control Type	Without lockable test button	
Utilisation coefficient	20 %	

## Complementary

J 2111 J 111 J	
Shape of pin	Flat
[Ui] rated insulation voltage	250 V IEC
	300 V CSA
	300 V UL
	300 V GE
[Uimp] rated impulse withstand voltage	2.5 kV 1.2/50 μs
Contacts material	Gold plated bifurcated silver
[le] rated operational current	2 A 28 V DC) NO IEC
	2 A 250 V AC) NO IEC
	1 A 28 V DC) NC IEC
	1 A 250 V AC) NC IEC
	3 A 28 V DC) UL
	3 A 277 V AC) UL
	SAZIT VACJUL
Maximum switching voltage	250 V IEC
resistive rated load	3 A 250 V AC
	3 A 28 V DC
Maximum switching capacity	750 VA/84 W
Minimum switching capacity	15 mW 3 mA, 5 V
Operating rate	<= 1200 cycles/hour under load
	<= 18000 cycles/hour no-load
Mechanical durability	10000000 cycles
Electrical durability	100000 cycles resistive depending on mounting position and working environment
verage coil consumption 0.9 W	

Price is "List Price" and may be subject to a trade discount – check with your local distributor or retailer for actual price.

Drop-out voltage threshold	>= 0.1 Uc	
operate time	20 ms	
release time	20 ms	
average coil resistance	2560 Ohm 20 °C +/- 10 %	
Rated operational voltage limits	38.452.8 V DC	
Protection category	RTI	
Test levels	Level A group mounting	
Operating position	Any position	
Net Weight	0.082 lb(US) (0.037 kg)	
device presentation	Complete product	

## **Environment**

Distriction at a second	
Dielectric strength	1300 V AC between contacts with micro disconnection
	2000 V AC between coil and contact
	2000 V AC between poles
Product Certifications	UL
	Lloyd's
	CE
	CSA
	GOST
	IECEE CB Scheme
Standards	UL 508
	IEC 61810-1
	CSA C22.2 No 14
Ambient Air Temperature for Storage	-40185 °F (-4085 °C)
Ambient air temperature for operation	-40131 °F (-4055 °C)
Vibration resistance	3 gn +/- 1 mm 10150 Hz)5 cycles in operation
	5 gn +/- 1 mm 10150 Hz)5 cycles not operating
IP degree of protection	IP40 conforming to IEC 60529
Shock resistance	10 gnin operation
	30 gnnot operating
Pollution degree	2

## Ordering and shipping details

Category	21127-ZELIO ICE CUBE RELAYS	
Discount Schedule	CP2	
GTIN	00785901491842	
Returnability	No	
Country of origin	CN	

## **Packing Units**

Unit Type of Package 1	PCE
Number of Units in Package 1	1

## **Contractual warranty**



**Green Premium**<sup>TM</sup> **label** is Schneider Electric's commitment to delivering products with best-inclass environmental performance. Green Premium promises compliance with the latest regulations, transparency on environmental impacts, as well as circular and low-CO<sub>2</sub> products.

**Guide to assessing product sustainability** is a white paper that clarifies global eco-label standards and how to interpret environmental declarations.

Learn more about Green Premium >

Guide to assess a product's sustainability >





Transparency RoHS/REACh

### Well-being performance

	Reach Free Of Svhc	
<b>②</b>	Toxic Heavy Metal Free	
<b>②</b>	Mercury Free	
<b>②</b>	Rohs Exemption Information	Yes

#### **Certifications & Standards**

Eu Rohs Directive	Pro-active compliance (Product out of EU RoHS legal scope)
	EU RoHS Declaration
China Rohs Regulation	China RoHS declaration
Environmental Disclosure	Product Environmental Profile
Weee	The product must be disposed on European Union markets following specific waste collection and never end up in rubbish bins.
Circularity Profile	End of Life Information
California Proposition 65	WARNING: This product can expose you to chemicals including: Nickel compounds, which is known to the State of California to cause cancer, and Di-isodecyl phthalate (DIDP), which is known to the State of California to cause birth defects or other reproductive harm. For more information go to www.P65Warnings.ca.gov