



## Alternate Catalog No. S202MUC-K1 Catalog No. 2CDS272061R0217

Description: MCB S200MUC 2P K 1A AC/DC

UPC No 4013614433122

Home > Modular DIN Rail Products > Mini Circuit breakers

The miniature circuit breaker S 200 M UC extends the established ABB System pro M compact® product range with an MCB for DC and AC applications. The S 200 M UC impresses with its performance range and the accordingly large amount of approvals. Its high inbuilt short circuit breaking capacity across the entire model line, its flexible AC and DC application and its approval and compliance in accordance with all major international and local standards make it truly unique. All current System pro M compact® accessories can be combined easily with the new model line. Whether warehousing or project engineering, planning, installing or maintaining your equipment, the S 200 M UC is a simple and flexible solution.

Descriptors	
Category	Mini Circuit breakers
Specifications	
Interrupting Rating acc. to UL1077	(500 V DC) 10 kA (480Y / 277 V AC) 6 kA
Number of Poles	2
Power Loss	2.7 W at Rated Operating Conditions per Pole 1.33 W
Product Main Type	S200MUC

rumber of roles	-
Power Loss	2.7 W at Rated Operating Conditions per Pole 1.33 W
Product Main Type	S200MUC
Rated Current	1 A
Rated Ultimate Short-Circuit Breaking Capacity	(220 V DC) 25 kA (440 V AC) 10 kA (440 V DC) 10 kA
Rated Voltage (V)	(500 V DC) (480Y / 277 V AC)
Standards	CSA 22.2 No. 235 IEC/EN 60947-2 UL 1077

Κ

electrification.us.abb.com Created on: 12/30/2024

Tripping Characteristic