



Alternate Catalog No. S203MUC-B50 Catalog No. 2CDS273061R0505

Description: MCB S200MUC 3P B 50A AC/DC

UPC No 4013614435119

Home > Circuit Breakers > Miniature Circuit Breakers > Supplementary Protectors

The miniature circuit breaker S 200 M UC extends the established ABB System pro M compact® product range with an MCB for DC and AC applications. The S 200 M UC impresses with its performance range and the accordingly large amount of approvals. Its high inbuilt short circuit breaking capacity across the entire model line, its flexible AC and DC application and its approval and compliance in accordance with all major international and local standards make it truly unique. All current System pro M compact® accessories can be combined easily with the new model line. Whether warehousing or project engineering, planning, installing or maintaining your equipment, the S 200 M UC is a simple and flexible solution.

Descriptors

Category	Supplementary Protectors
----------	--------------------------

Specifications

Number of Poles	3
Tripping Characteristic	B
Rated Current	50 A
Standards	IEC/EN 60898-1 IEC/EN 60947-2
Product Main Type	S200MUC
Rated Voltage (V)	(500 V DC) (480Y / 277 V AC)
Interrupting Rating acc. to UL1077	(500 V DC) 10 kA (480Y / 277 V AC) 6 kA
Rated Short-Circuit Capacity	(253 V AC) 10 kA (400 V AC) 10 kA (440 V DC) 10 kA
Rated Ultimate Short-Circuit Breaking Capacity	(220 V DC) 25 kA (440 V AC) 6 kA (440 V DC) 10 kA
Power Loss	13.4 W at Rated Operating Conditions per Pole 4.48 W