

S203PR-K1,6



Products Low Voltage Products and Systems Modular DIN Rail Products Miniature Circuit Breakers MCBs

General Information

Extended Product Type:	S203PR-K1,6
Product ID:	2CDS273427R0257
EAN:	4016779847414
Catalog Description:	Miniature Circuit Breaker - S200PR - 3P - K
Long Description:	S203PR-K1,6 MCB K-Char., 10kA, 1,6A, 3P, RTT UL 1077, Ring Cable Lug

Additional Information

Actuator Material:	Insulation Group II, Black, Sealable
Actuator Type:	Insulation group II, black, sealable
Ambient Air Temperature:	Operation -25 ... +55 °C Storage -40 ... +70 °C
Built-In Depth (t₂):	69 mm
Connecting Capacity UL/CSA:	Conductor 14-4 AWG
Contact Position Indication:	Red ON / Green OFF
Country of Origin:	Germany (DE)
Customs Tariff Number:	85362010
Data Sheet, Technical Information:	2CDC002138D0201
Declaration of Conformity - CE:	2CDK400586D2702
Degree of Protection:	IP20
Dielectric Test Voltage:	50 / 60 Hz, 1 min: 2 kV
EAN:	4016779847414
EPLAN Catalog Tree:	Electrical engineering / Protection devices / General
ETIM 4:	EC000042 - Miniature circuit breaker (MCB)
ETIM 5:	EC000042 - Miniature circuit breaker (MCB)
ETIM 6:	EC000042 - Miniature circuit breaker (MCB)
Electrical Endurance:	20000 AC cycle
Energy Limiting Class:	3
Environmental Conditions:	28 cycles with 55 °C / 90-96 % and 25 °C / 95-100 %
Environmental Information:	2CDK400030D201
Housing Material:	Insulation Group I, RAL 7035
Installation Size:	acc. to DIN 43880 2
Instructions and Manuals:	2CDC002138D0201
Interrupting Rating acc. to UL1077:	(480Y / 277 V AC) 10 kA
Invoice Description:	S203PR-K1,6 MCB K-Char., 10kA, 1,6A, 3P, RTT
Maximum Operating Voltage UL/CSA:	480Y / 277 V AC
Mechanical Endurance:	20000 cycle
Minimum Order Quantity:	1 piece
Mounting Position:	Any
Mounting on DIN Rail:	TH35-7.5 (35 x 7.5 mm Mounting Rail) acc. to IEC 60715 TH35-15 (35 x 15 mm Mounting Rail) acc. to IEC 60715
Number of Poles:	3
Number of Protected Poles:	3
Object Classification Code:	F
Operational Voltage:	Minimum 12 V AC

Options Provided:	Ring tongue
Overvoltage Category:	III
Package Level 1 EAN:	4016779849418
Package Level 1 Gross Weight:	1.32 kg
Package Level 1 Height:	82 mm
Package Level 1 Length:	191 mm
Package Level 1 Units:	3 piece
Package Level 1 Width:	121 mm
Package Level 2 EAN:	4016779982924
Pole Net Weight:	0.125 kg
Pollution Degree:	2
Power Loss:	4.68 W at Rated Operating Conditions per Pole 1.56 W
Power Supply Connection:	Arbitrary
Product Main Type:	S200PR
Product Name:	Miniature Circuit Breaker
Product Net Depth:	71 mm
Product Net Height:	100 mm
Product Net Weight:	0.42 kg
Product Net Width:	52.5 mm
Rated Current (I_n):	1.6 A
Rated Frequency (f):	50 Hz 60 Hz
Rated Impulse Withstand Voltage (U_{imp}):	4 kV (6.2 kV @ sea level) (5.0 kV @ 2000 m)
Rated Insulation Voltage (U_i):	acc. to IEC/EN 60664-1 500 V
Rated Operational Voltage:	acc. to IEC 60947-2 400 V AC
Rated Service Short-Circuit Breaking Capacity (I_{cs}):	(400 V AC) 11.2 kA
Rated Ultimate Short-Circuit Breaking Capacity (I_{cu}):	(400 V AC) 15 kA
Recommended Screw Driver:	Pozidriv 2
Reference Ambient Air Temperature:	20 °C
Remarks:	IP40 in enclosure with cover
Resistance to Shock acc. to IEC 60068-2-27:	25g / 2 shocks / 13 ms
Resistance to Vibrations acc. to IEC 60068-2-6:	5g, 20 cycles at 5 ... 150 ... 5 Hz with load 0.8 In
Screw Terminal Type:	Ring-Tongue Terminal with Captive Screw
Selling Unit of Measure:	piece
Standards:	CSA 22.2 No. 235 IEC/EN 60947-2 UL 1077
Terminal Type:	Ring-Tongue Terminals
Tightening Torque:	2.8 N·m
Tightening Torque UL/CSA:	25 in·lb
Tripping Characteristic:	K
UNSPSC:	39121614
Width in Number of Modular Spacings:	3
eClass:	7.0 27141901

Accessories Available: Yes

Actuator Marking: I / O

