



Figure similar

SIEMENS LOW VOLTAGE ES SERIES LOAD CENTER. MAIN LUG WITH 24 1-Inch Spaces ALLOWING MAX 40 CIRCUITS. 1-PHASE 3-WIRE SYSTEM RATED 120/240V(125A) 100KA INTERRUPT. SPECIAL FEATURES: ALUMINUM BUS, FACTORY INSTALLED GROUND BAR, GRAY TRIM, NEMA TYPE1 ENCLOSURE FOR INDOOR USE. REPLACED BY SN2448L1125. AVAILABLE 4/1/2020

General technical data

| | |
|------------------------------|--------------------|
| configuration of the busbars | #NO_D AT A# |
| phase number | 1 |
| suitability for operation | CIRCUIT PROTECTION |

Electricity

| | |
|---|-------|
| ampacity | 225 A |
| ampacity minimum | 225 A |
| voltage between phase and phase rated value | 240 V |

Switching capacity

| | |
|--|---------|
| switching capacity current according to EN 60898 rated value | 25000 A |
|--|---------|

Model

| | |
|--------------------------|--|
| product brand name | Siemens |
| product sub brand name | QR |
| product type designation | CIRCUIT BREAKER |
| special product feature | FIELD INSTALLABLE INTERNAL ACCESSORIES |

Mechanical Design

| | |
|--|---|
| number of modular width units for installation width | 0 |
|--|---|

General product approval

| | |
|----------------------------|-----------------|
| certificate of suitability | UL 489/CSA 22.2 |
|----------------------------|-----------------|

last modified: 6/18/2021 

