



Catalog Number: S281UC-C20
UPC Number: 88861424320
Status: Active
Replacement Catalog: S201MUC-C20

Miniature Circuit Breaker, Supplemental Protector, Rated Current 20 Amps, 1 Pole, Interrupt Rating 6 kA (IEC, CSA 22.2 No. 235) and 10 kA UL 1077, Thermal Magnetic Trip Curve C, Electromechanic and/or Thermal Tripping Mechanism for Short Circuit Protection, Voltage up to 250/500 VDC, DIN Rail Mounted, Finger Safe and Multi-Function Terminals

North American Specifications (UNSPSC)

| | |
|-----------------------|--|
| UNSPSC | 39121603 Miniature circuit breakers |
| IGCC | 4897 Miniature circuit breakers |
| Brand Name | ABB |
| Type | High Performance MCB Provides Compact Supplementary, Energy Limiting, Circuit Protection |
| Special Features | DIN Rail Mounting, Finger Safe and Multi-Function Terminals |
| Application | Designed for Use with Medium Magnetic Start Up Currents; Example: Lighting, Control Panels |
| Standard | UL 1077, CSA 22.2 No. 235 |
| Voltage Rating | 250/500 VDC |
| Amperage Rating | 20 Amps |
| Frequency Rating | 50/60 Hertz |
| Trip Type | C |
| Interrupt Rating | 6 kA |
| Number Of Poles | 1 |
| Auxiliary Contacts | Yes |
| Length | 68 mm |
| Width | 17.5 mm |
| Height | 90 mm |
| Operating Temperature | -25 to +55 Degrees Celcius |

Packaging

| | |
|---------------------------|----------------|
| Inner Quantity | 1 |
| Inner Dimensions (inches) | .72x4.13x3.15 |
| Outer Quantity | 10 |
| Outer Dimensions (inches) | 7.2x4.13x3.15 |
| Weight Uom | 0.61 lbs. Each |