



Representative

Catalog Number: S282UC-K6FS
UPC Number: 804325565134
Status: Active

Miniature Circuit Breaker, Supplemental Protector, Rated Current 6 Amps, 2 Pole, Interrupt Rating 6 kA (IEC, CSA 22.2 No. 235) and 10 kA UL 1077, Thermal Magnetic Trip Curve K, Electromechanic and/or Thermal Tripping Mechanism for Short Circuit Protection, Voltage up to 250/500 VDC, DIN Rail Mounted (FS Series), Finger Safe and Multi-Function Terminals

North American Specifications (UNSPSC)

UNSPSC	39121603 Miniature circuit breakers
IGCC	4897 Miniature circuit breakers
Brand Name	ABB
Type	High Performance MCB Provides Compact Supplementary, Energy Limiting, Circuit Protection
Special Features	DIN Rail Mounting, Finger Safe and Multi-Function Terminals
Application	Designed for Allowing Higher In-Rush Current During System Start Up; Example: Motors, Transformers
Standard	UL 1077, CSA 22.2 No. 235
Voltage Rating	250/500 VDC
Amperage Rating	6 Amps
Frequency Rating	50/60 Hertz
Trip Type	K
Interrupt Rating	6 kA
Number Of Poles	2
Auxiliary Contacts	Yes
Length	68 mm
Width	35 mm
Height	90 mm
Operating Temperature	-25 to +55 Degrees Celcius

Packaging

Inner Quantity	1
Outer Quantity	3
Outer Dimensions (inches)	4.33x3.78x3.23
Weight Uom	62.19 lbs. per 100