



Figure similar

SIEMENS LOW VOLTAGE ES SERIES LOAD CENTER. MAIN LUG WITH 30 1-Inch Spaces ALLOWING MAX 30 CIRCUITS. 1-PHASE 3-WIRE SYSTEM RATED 120/240V(200A) 100KA INTERRUPT. SPECIAL FEATURES: ALUMINUM BUS, GRAY TRIM, NEMA TYPE1 ENCLOSURE FOR INDOOR USE. REPLACED BY SN3030L1200. AVAILABLE 4/1/2020

General technical data

|                              |             |
|------------------------------|-------------|
| configuration of the busbars | 200 A       |
| fastening method             | Combination |
| phase number                 | 1           |
| suitability for operation    | Residential |

Electricity

|                                                    |       |
|----------------------------------------------------|-------|
| ampacity                                           | 200 A |
| ampacity minimum                                   | 200 A |
| voltage between phase and Ground (GND) rated value | 120 V |
| voltage between phase and phase rated value        | 240 V |

Switching capacity

|                                                              |         |
|--------------------------------------------------------------|---------|
| switching capacity current according to EN 60898 rated value | 22000 A |
|--------------------------------------------------------------|---------|

Model

|                        |              |
|------------------------|--------------|
| product brand name     | Siemens      |
| product sub brand name | Load Centers |

Mechanical Design

|                                                      |    |
|------------------------------------------------------|----|
| number of modular width units for installation width | 30 |
|------------------------------------------------------|----|

last modified:

1/6/2021 

