



Figure similar

SIEMENS LOW VOLTAGE ES SERIES LOAD CENTER. MAIN LUG WITH 30 1-Inch Spaces ALLOWING MAX 30 CIRCUITS. 1-PHASE 3-WIRE SYSTEM RATED 120/240V(200A) 100KA INTERRUPT. SPECIAL FEATURES: ALUMINUM BUS, WHITE TRIM, NEMA TYPE1 ENCLOSURE FOR INDOOR USE. REPLACED BY SN3030L1200W. AVAILABLE 4/1/2020

General technical data

configuration of the busbars	200 A
phase number	1

Electricity

ampacity	200 A
ampacity minimum	200 A
voltage between phase and Ground (GND) rated value	120 V
voltage between phase and phase rated value	240 V

Switching capacity

switching capacity current according to EN 60898 rated value	100000 A
--	----------

Model

product brand name	Siemens
product type designation	Series ES; Main Lug/Convertible
special product feature	Features: Invertible for bottom feed application; Combination head screw on the neutrals; ground; trim; upper pan; and bond screw provide installation flexibility; The prepositioned bond screw eliminates bond strap/ screw assemblies; and reduces the risk

Mechanical Design

number of modular width units for installation width	30
--	----

General product approval

certificate of suitability	UL Listed
----------------------------	-----------

last modified: 6/18/2021 

