



Catalog Number: S502-B32
UPC Number: 66201953566
Status: Active

Miniature Circuit Breaker, Supplemental Protector, Rated Current 32 Amps, 2 Pole, Interrupt Rating 30 kA, Thermal Magnetic Trip Curve B, Electromechanic and/or Thermal Tripping Mechanism for Short Circuit Protection, Voltage up to 277/Y600 VAC (UL 1077) and 690 VAC (IEC), DIN Rail Mounted, Finger Safe and Multi-Function Terminals, CSA 22.2

North American Specifications (UNSPSC)

| | |
|-----------------------|--|
| UNSPSC | 39121603 Miniature circuit breakers |
| IGCC | 4897 Miniature circuit breakers |
| Brand Name | ABB |
| Type | High Performance MCB Provides Compact Supplementary, Energy Limiting, Circuit Protection |
| Special Features | DIN Rail Mounting, Finger Safe and Multi-Function Terminals |
| Application | Designed for Allowing Higher In-Rush Current During System Start Up; Example: Motors, Transformers |
| Standard | UL 1077, CSA 22.2 No. 235, VDE 0641/6.78 |
| Voltage Rating | 277/Y600 VAC (UL1077), 690 VAC (IEC) |
| Amperage Rating | 32 Amps |
| Frequency Rating | 50/60 Hertz |
| Trip Type | B |
| Interrupt Rating | 30 kA |
| Number Of Poles | 2 |
| Auxiliary Contacts | Yes |
| Length | 86 mm |
| Width | 50 mm |
| Height | 92 mm |
| Operating Temperature | -40 Degrees Celcius |

Packaging

| | |
|---------------------------|-------------|
| Outer Quantity | 1 |
| Outer Dimensions (inches) | 1x1x1 |
| Weight Uom | 1 lbs. Each |