



Catalog Number: S504UC-K0.58
UPC Number: 88861414114
EAN Number: 07612270302796
Status: Active

Miniature Circuit Breaker, Supplemental Protector, Rated Current 0.58 Amps, 4 Pole, Interrupt Rating 30 kA, Thermal Magnetic Trip Curve K, Electromechanic and/or Thermal Tripping Mechanism for Short Circuit Protection, Voltage up to 600 VDC Per Pole (UL 1077) and 750 VDC (IEC), DIN Rail Mounted, Finger Safe and Multi-Function Terminals, CSA 22.2

North American Specifications (UNSPSC)

UNSPSC	39121603 Miniature circuit breakers
IGCC	4897 Miniature circuit breakers
Brand Name	ABB
Type	High Performance MCB Provides Compact Supplementary, Energy Limiting, Circuit Protection
Special Features	DIN Rail Mounting, Finger Safe and Multi-Function Terminals
Application	Designed for Allowing Higher In-Rush Current During System Start Up; Example: Motors, Transformers
Standard	UL 1077, CSA 22.2, VDE 0660, 60947-2
Voltage Rating	600 VDC Per Pole (UL 1077) and 750 VDC (IEC)
Amperage Rating	8 Amps
Frequency Rating	50/60 Hertz
Trip Type	K
Interrupt Rating	30 kA
Number Of Poles	4
Auxiliary Contacts	Yes
Length	86 mm
Width	100 mm
Height	92 mm
Operating Temperature	-40 Degrees Celcius

Packaging

Outer Quantity	1
Outer Dimensions (inches)	7.874x3.701x4.016
Weight Uom	2.13 lbs. Each