

General Information

Extended Product Type:	S801U-K15
Product ID:	2CCS881017R0457
EAN:	7612271214043
Catalog Description:	High Performance Circuit Breaker - S800U - Tripping characteristic K - Number of poles 1 - Rated operational current 15A - Rated operational voltage 240V AC
Long Description:	S801U-K15 1 Pole K Characteristic 15A 30kA 240/415VAC High Performance Circuit Breaker HPCB

Categories

Products » Low Voltage Products and Systems » Modular DIN Rail Products » High Performance Circuit Breakers HPCBs

Ordering

EAN:	7612271214043
Minimum Order Quantity:	1 piece
Customs Tariff Number:	85362020

Dimensions

Product Net Width:	27 mm
Product Net Depth:	82.5 mm
Product Net Height:	95 mm
Product Net Weight:	0.25 kg

Container Information

Package Level 1 Units:	1 piece
Package Level 1 Width:	105 mm
Package Level 1 Length:	33 mm
Package Level 1 Height:	99 mm
Package Level 1 Gross Weight:	0.27 kg
Package Level 1 EAN:	7612271214043

Environmental

Ambient Air Temperature:	Operation -25 ... +60 °C Storage -40 ... +70 °C
RoHS Status:	Following EU Directive 2002/95/EC August 18, 2005 and amendment

Technical

Standards:	IEC 60947-2_UL489_CSA22.2 NO.5-02
Number of Poles:	1
Tripping Characteristic:	K
Rated Current (I _n):	15
Rated Operational Voltage:	240 V AC
Power Loss:	2.7 W
Rated Ultimate Short-Circuit Breaking Capacity (I _{cu}):	(240 V AC) 30 kA
Rated Service Short-Circuit Breaking Capacity (I _{cs}):	(240 V AC) 25 kA
Contact Position Indication:	ON / OFF / TRIP
Connecting Capacity:	Flexible 1 ... 50 mm ² Flexible Stranded 1 ... 70 mm ²

Certificates and Declarations (Document Number)

Declaration of Conformity - CE:	2CCC413033D0601
RoHS Information:	2CCC413008D0201

Classifications

ETIM 4.0:	EC000042 - Miniature circuit breaker (MCB)
ETIM 5.0:	EC000042 - Miniature circuit breaker (MCB)
Object Classification Code:	F

