
PRODUCT-DETAILS

S803PV-SP100

S803PV-SP100 High Performance MCB



General Information

Extended Product Type	S803PV-SP100
Product ID	2CCF019620R0001
EAN	7612271471651
Catalog Description	S803PV-SP100 High Performance MCB
Long Description	<p>The S803PV-SP100 is a 3-pole High Performance Circuit breaker for photovoltaics (DC) with B-characteristic, with cage terminal and a rated current of 100 A. It is a current limiting device with a maximum breaking capacity of 5kA at 1200V. It can be used for voltages up to 1200V DC. It has two different tripping mechanisms, the thermal tripping mechanism for overload protection and the electromechanic tripping mechanism for short circuit protection. The S803PV-SP100 complies with IEC/EN 60947-2 and allows the use for industrial applications. It has numerous of approvals, therefore it can be used worldwide. The extensive range of accessory makes the use of S803PV-SP100 more comfortable. Due to the fast arc extinction of S803PV-SP100 your application will be secured.</p>

Technical

Standards	IEC/EN 60947-2
Number of Poles	3
Number of Protected Poles	3
Tripping Characteristic	B
Rated Current (I_n)	100 A
Rated Operational Voltage	1200 V DC
Power Loss	24 W at Rated Operating Conditions per Pole 8 W

Rated Insulation Voltage (Ui)	1500 V
Rated Short-Circuit Capacity (Icn)	(400 V) 5 kA (230 V) 5 kA
Rated Ultimate Short-Circuit Breaking Capacity (Icu)	(1200 V DC) 5 kA
Rated Service Short-Circuit Breaking Capacity (Ics)	(1200 V DC) 5 kA
Energy Limiting Class	3
Overvoltage Category	III
Pollution Degree	2
Rated Impulse Withstand Voltage (Uiimp)	8 kV
Degree of Protection	IP20
Connecting Capacity	Rigid 0 ... 50 mm ² Flexible 0 ... 70 mm ²
Built-In Depth (t2)	111 mm

Environmental

Ambient Air Temperature	Operation -25...60 °C
RoHS Status	Following EU Directive 2011/65/EU

Dimensions

Product Net Width	81 mm
Product Net Depth / Length	82.5 mm
Product Net Height	95 mm
Product Net Weight	735 g

Container Information

Package Level 1 Units	box 1 piece
Package Level 1 Width	105 mm
Package Level 1 Depth / Length	86 mm
Package Level 1 Height	99 mm
Package Level 1 Gross Weight	770 g
Package Level 1 EAN	7612271471651

Ordering

Minimum Order Quantity	1 piece
Customs Tariff Number	85352120

Certificates and Declarations (Document Number)

Declaration of Conformity - CE	2CCC413058D0201
Environmental Information	2CCY413207D0203
Instructions and	2CCC413016M0008

Manuals

RoHS Information

[2CCC413058D0201](#)
[9AKK107680A3903](#)

Popular Downloads

Data Sheet, Technical
Information[2CCC413003C0208](#)Instructions and
Manuals[2CCC413016M0008](#)

Classifications

Object Classification
Code

F

ETIM 6

[EC000042 - Miniature circuit breaker \(MCB\)](#)

ETIM 7

[EC000042 - Miniature circuit breaker \(MCB\)](#)

Categories

Low Voltage Products and Systems → Modular DIN Rail Products → High Performance Circuit Breakers HPCBs

