



S8VK-G06024

Fuente de alimentación 60W/24V/2.5A carril DIN

Type	Book type
Mounting method	DIN rail
Phase	Single
Power output	60 W
Efficiency	88 %
Output voltage	24 V
Rated output current	2.5 A
Power boost ratio	120 %
Temperature range	-40-70 °C
Terminal	Screw
Communication port(s)	None
Alarm function	-
Number of output branches	1
Rated supply voltage at AC 50 Hz	100-240 V
Allowable supply voltage AC	85-264 V
Allowable supply voltage DC	90-350 V
Product Width (unpacked)	32 mm
Product Height (unpacked)	90 mm
Product Depth (unpacked)	110 mm

Productos relacionados:



Disyuntor electrónico

S8V-CP - Disyuntor electrónico



S8V-NF

Filtro de ruido S8V-NF

Descargas

Librería CAD



Perfect Power Supply Solutions

Catálogo

ES PDF 800 KB



S8VK-G Switch Mode Power Supply

Datasheet

EN PDF 10 MB



S8VK-S/S8FS-G

Catálogo

EN PDF 7 MB

TÉRMINOS DE USO DEL SITIO WEB

Este documento PDF se generó a partir del sitio web europeo de OMRON Industrial Automation el 5 September, 2023. Haga clic aquí para acceder a los [legal](#).

OMRON

INDUSTRIAL AUTOMATION | [INDUSTRIAL.OMRON.EU](https://www.industrial.omron.eu)