SIEMENS

Data sheet US2:SN351CR



Siemens Low Voltage Talon Meter Sockets Residential - Talon Meter Sockets UAS8/9 Aluminum are Residential Enclosures Single-Family Metering. Type: UAS8/9 Features: NO BYPASS Application: RESIDENTIAL Std: UL V. Rating: 300V A. Rating: 100A Phase: 1 OR 3 PHASE Size: 5.0 x 17.2 x 30.8 No Of Cutouts: 13 Cutout Size: 2 x 2.750, 9 x (1, 1-1/4, 1-1/2, 2), 2 x (1/2, 3/4, 1, 1-1/4, 1-1/2) Cable Entry: OH Terminals: 5. Surface mounting. Operating Temperature: Avg AMBIENT Enclosure: AL

General technical data	
cable entry type	ОН
fastening method	SURFACE MOUNTING
number of openings	13
suitability for operation	RESIDENTIAL
Electricity	
ampacity	100 A
voltage between phase and phase rated value	300 V
Model	
product brand name	MURRAY
product type designation	UAS8/9
special product feature	NO BYPASS
Mechanical Design	
depth [in]	30.8 in
design of the terminal strip	5
height [in]	5 in
width [in]	17.2 in
General product approval	
certificate of suitability	UL

last modified: 5/18/2022 🖸