Product datasheet

Specifications





heat sink for panel mounting relay

SSRHD10

Main

Range Of Product	Harmony Solid State Relays
Product Or Component Type	Heat sink

Complementary

J	
Product Compatibility	1 solid state relay SSR on panel
Thermal Resitance	1 °C/W
Mounting Support	DIN rail
Material	Aluminium
Surface Finish	Black anodized
Surface And Useful Surface	1425 cm ²
Number Of Mounting Holes	6 with UNC 8-32 thread
Tightening Torque	1.72.2 N.m
Sale Per Indivisible Quantity	1
Width	76.2 mm
Height	132.1 mm
Depth	60.2 mm
Net Weight	0.630 kg

Packing Units

•	
Unit Type Of Package 1	PCE
Number Of Units In Package 1	1
Package 1 Height	7.7 cm
Package 1 Width	27.0 cm
Package 1 Length	28.7 cm
Package 1 Weight	2.95 kg
Unit Type Of Package 2	S03
Number Of Units In Package 2	22
Package 2 Height	30.0 cm
Package 2 Width	30.0 cm
Package 2 Length	40.0 cm
Package 2 Weight	64.9 kg

Price is "List Price" and may be subject to a trade discount - check with your local distributor or retailer for actual price.

Sustainability Screen Premium

Green PremiumTM label is Schneider Electric's commitment to delivering products with best-inclass environmental performance. Green Premium promises compliance with the latest regulations, transparency on environmental impacts, as well as circular and low-CO₂ products.

Guide to assessing product sustainability is a white paper that clarifies global eco-label standards and how to interpret environmental declarations.

Learn more about Green Premium >

Guide to assess a product's sustainability >



RoHS/REACh

Well-being performance

Reach Free Of Svhc
Toxic Heavy Metal Free
Mercury Free
Rohs Exemption Information Yes

Certifications & Standards

Reach Regulation	REACh Declaration
Eu Rohs Directive	Pro-active compliance (Product out of EU RoHS legal scope) EU RoHS Declaration
China Rohs Regulation	China RoHS declaration
Circularity Profile	No need of specific recycling operations

Product datasheet

SSRHD10

Dimensions Drawings

Dimensions

