



PRODUCT-DETAILS

# ST201M-B35NA

## Miniature Circuit Breaker - ST200M - 1P+N - 35 A - B



| General Information   |                                                                                                             |
|-----------------------|-------------------------------------------------------------------------------------------------------------|
| Extended Product Type | ST201M-B35NA                                                                                                |
| Product ID            | 2CDS271335R0355                                                                                             |
| EAN                   | 4016779029971                                                                                               |
| Catalog Description   | Miniature Circuit Breaker - ST200M - 1P+N - 35 A - B                                                        |
| Long Description      | ST201M-B35NA Miniature Circuit Breaker ST201M-B35NA Miniature Circuit Breaker B-Char., 10kA, 35A, 1P, 1P+NA |

| Technical                                           |                                               |
|-----------------------------------------------------|-----------------------------------------------|
| Standards                                           | CSA 22.2 No. 235<br>IEC/EN 60947-2<br>UL 1077 |
| Tripping Characteristic                             | B                                             |
| Rated Operational Voltage                           | acc. to IEC 60947-2 230 V AC                  |
| Rated Insulation Voltage (U <sub>i</sub> )          | acc. to IEC/EN 60664-1 440 V                  |
| Rated Impulse Withstand Voltage (U <sub>imp</sub> ) | 4 kV                                          |
| Input Voltage Type                                  | AC                                            |
| Rated Current (I <sub>n</sub> )                     | 35 A                                          |

|                                                                   |                                               |
|-------------------------------------------------------------------|-----------------------------------------------|
| Rated Ultimate Short-Circuit Breaking Capacity (I <sub>cu</sub> ) | (230 V AC) 15 kA<br>(230 V) 15 kA             |
| Rated Conditional Short-Circuit Current (I <sub>nc</sub> )        | (230 V) 15 kA<br>(400 V) 15 kA                |
| Rated Service Short-Circuit Breaking Capacity (I <sub>cs</sub> )  | (230 V AC) 11.2 kA                            |
| Rated Frequency (f)                                               | 50 / 60 Hz                                    |
| Energy Limiting Class                                             | 3                                             |
| Number of Protected Poles                                         | 1                                             |
| Number of Poles                                                   | 1P+N                                          |
| Overvoltage Category                                              | III                                           |
| Accessories Available                                             | Yes                                           |
| Connecting Capacity                                               | Flexible 25 ... 25 mm²<br>Rigid 35 ... 35 mm² |
| Terminal Type                                                     | Double Clamp                                  |

Material Compliance

|                                             |                                                                        |
|---------------------------------------------|------------------------------------------------------------------------|
| RoHS Information                            | 2CDK400679D2703                                                        |
| RoHS Status                                 | Following EU Directive 2011/65/EU and Amendment 2015/863 July 22, 2019 |
| RoHS Date                                   | 20221214                                                               |
| REACH Declaration                           | 9AKK107492A1906                                                        |
| REACH Information                           | True - contains substances > 0.1 mass percentage                       |
| REACH Date                                  | 20240821                                                               |
| Conflict Minerals Reporting Template (CMRT) | 9AKK108468A3363                                                        |

Environmental

|                         |                          |
|-------------------------|--------------------------|
| Ambient Air Temperature | Operation -25 ... +55 °C |
| Degree of Protection    | IP20                     |
| Pollution Degree        | 3                        |

Technical UL/CSA

|                                    |                 |
|------------------------------------|-----------------|
| Interrupting Rating acc. to UL1077 | (277 V AC) 5 kA |
|------------------------------------|-----------------|

Dimensions

|                                     |         |
|-------------------------------------|---------|
| Width in Number of Modular Spacings | 2.0     |
| Product Net Width                   | 35 mm   |
| Product Net Height                  | 88 mm   |
| Product Net Depth / Length          | 69 mm   |
| Product Net Weight                  | 0.23 kg |
| Built-In Depth (t <sub>2</sub> )    | 69 mm   |

Ordering

|                              |                |
|------------------------------|----------------|
| Package Level 1 Units        | carton 1 piece |
| Package Level 1 Gross Weight | 0.26 kg        |

Certificates and Declarations

|                                     |                        |
|-------------------------------------|------------------------|
| Declaration of Conformity<br>- CE   | 2CDK400679D2703        |
| Declaration of Conformity<br>- UKCA | 9AKK108467A5200        |
| Certification Agency                | CSA<br>EN<br>IEC<br>UL |

Installation

|                          |                 |
|--------------------------|-----------------|
| Instructions and Manuals | 9AKK107046A3150 |
|--------------------------|-----------------|

Popular Downloads

|                                      |                 |
|--------------------------------------|-----------------|
| Data Sheet, Technical<br>Information | 9AKK107046A3150 |
|--------------------------------------|-----------------|

Classifications

|                                       |                                                            |
|---------------------------------------|------------------------------------------------------------|
| ETIM 8                                | EC000042 - Miniature circuit breaker (MCB)                 |
| ETIM 9                                | EC000042 - Miniature circuit breaker (MCB)                 |
| WEEE Category                         | 5. Small Equipment (No External Dimension More Than 50 cm) |
| WEEE B2C / B2B                        | Business To Business                                       |
| CN8                                   | 8536 20 10                                                 |
| UNSPSC                                | 39121603                                                   |
| eClass                                | V11.0 : 27141901                                           |
| IDEA Granular Category<br>Code (IGCC) | 4899 >> Miniature circuit breaker (MCB) screw-in model     |

Categories

Low Voltage Products and Systems → Modular DIN Rail Products → Miniature Circuit Breakers MCBs → Miniature Circuit Breakers MCBs

