



PRODUCT-DETAILS

ST202M-B1

Miniature Circuit Breaker - ST200M - 2P - 1 A - B



General Information	
Extended Product Type	ST202M-B1
Product ID	2CDS272334R0015
EAN	4016779021043
Catalog Description	Miniature Circuit Breaker - ST200M - 2P - 1 A - B
Long Description	ST202M-B1 Miniature Circuit Breaker ST202M-B1 Miniature Circuit Breaker B-Char., 10kA, 1A, 2P

Technical	
Standards	CSA 22.2 No. 235 IEC/EN 60947-2 UL 1077
Tripping Characteristic	B
Rated Operational Voltage	acc. to IEC 60947-2 400 V AC
Rated Insulation Voltage (U _i)	acc. to IEC/EN 60664-1 440 V
Rated Impulse Withstand Voltage (U _{imp})	4 kV

)

Input Voltage Type	AC
Rated Current (I _n)	1 A
Rated Ultimate Short-Circuit Breaking Capacity (I _{cu})	(125 V DC) 15 kA (400 V AC) 15 kA (400 V) 15 kA
Rated Conditional Short-Circuit Current (I _{nc})	(230 V) 15 kA (400 V) 15 kA
Rated Service Short-Circuit Breaking Capacity (I _{cs})	(400 V AC) 11.2 kA
Rated Frequency (f)	50 / 60 Hz
Energy Limiting Class	3
Number of Protected Poles	2
Number of Poles	2P
Overvoltage Category	III
Accessories Available	Yes
Connecting Capacity	Flexible 25 ... 25 mm ² Rigid 35 ... 35 mm ²
Terminal Type	Double Clamp

Material Compliance

RoHS Information	2CDK400679D2703
RoHS Status	Following EU Directive 2011/65/EU and Amendment 2015/863 July 22, 2019
RoHS Date	20221214
REACH Declaration	9AKK107492A1906
REACH Information	True - contains substances > 0.1 mass percentage
REACH Date	20240821
Conflict Minerals Reporting Template (CMRT)	9AKK108468A3363

Environmental

Ambient Air Temperature	Operation -25 ... +55 °C
Degree of Protection	IP20
Pollution Degree	3

Technical UL/CSA

Interrupting Rating acc. to UL1077	(125 V DC) 10 kA (480Y / 277 V AC) 10 kA
------------------------------------	---

Dimensions

Width in Number of Modular Spacings	2.0
Product Net Width	35 mm
Product Net Height	88 mm
Product Net Depth / Length	69 mm
Product Net Weight	0.23 kg

Built-In Depth (t ₂)	69 mm
----------------------------------	-------

Ordering

Package Level 1 Units	carton 1 piece
Package Level 1 Gross Weight	0.26 kg

Certificates and Declarations

Declaration of Conformity - CE	2CDK400679D2703
Declaration of Conformity - UKCA	9AKK108467A5200
Certification Agency	CSA EN IEC UL

Installation

Instructions and Manuals	9AKK107046A3150
--------------------------	-----------------

Popular Downloads

Data Sheet, Technical Information	9AKK107046A3150
-----------------------------------	-----------------

Classifications

ETIM 8	EC000042 - Miniature circuit breaker (MCB)
ETIM 9	EC000042 - Miniature circuit breaker (MCB)
WEEE Category	5. Small Equipment (No External Dimension More Than 50 cm)
WEEE B2C / B2B	Business To Business
CN8	8536 20 10
UNSPSC	39121603
eClass	V11.0 : 27141901
IDEA Granular Category Code (IGCC)	4899 >> Miniature circuit breaker (MCB) screw-in model

Categories

Low Voltage Products and Systems → Modular DIN Rail Products → Miniature Circuit Breakers MCBs → Miniature Circuit Breakers MCBs

