



PRODUCT-DETAILS

SU204M-C6

Miniature Circuit Breaker - SU200M - 4P - 6 A - C



General Information	
Extended Product Type	SU204M-C6
Product ID	2CDS274337R0064
EAN	4016779931502
Catalog Description	Miniature Circuit Breaker - SU200M - 4P - 6 A - C
Long Description	SU204M-C6 Miniature Circuit Breaker C-Char., 10kA, 6A, 4P UL489

Technical	
Tripping Characteristic	C
Rated Operational Voltage	acc. to IEC 60898-1 480 V acc. to IEC 60947-2 400 V AC
Rated Insulation Voltage (U _i)	acc. to IEC/EN 60664-1 440 V
Rated Impulse Withstand Voltage (U _{imp})	4 kV at 2000 m 5 kV at Sea Level 6.2 kV
Input Voltage Type	AC/DC
Rated Current (I _n)	6 A
Rated Short-Circuit	(400 V AC) 11.2 kA

Capacity		
Rated Ultimate Short-Circuit Breaking Capacity (I_{cu})	(400 V AC) 15 kA (400 V) 15 kA	
Rated Conditional Short-Circuit Current (I_{nc})	(400 V) 15 kA	
Rated Service Short-Circuit Breaking Capacity (I_{cs})	(400 V AC) 11.2 kA	
Rated Frequency (f)	50 / 60 Hz DC	
Power Loss	8 W at Rated Operating Conditions per Pole 2 W	
Power Supply Connection	Arbitrary	
Contact Position Indication	Red ON / Green OFF	
Energy Limiting Class	3	
Mechanical Endurance	20000 cycle	
Number of Protected Poles	4	
Number of Poles	4P	
Overvoltage Category	III	
Tightening Torque	2.8 N·m	
Screw Terminal Type	Failsafe Bi-directional Cylinder-lift Terminal	
Actuator Marking	I / O	
Actuator Material	Insulation Group II, Black, Sealable	
Housing Material	Insulation Group I, RAL 7035	
Mounting on DIN Rail	TH35-15 (35 x 15 mm Mounting Rail) acc. to IEC 60715 TH35-7.5 (35 x 7.5 mm Mounting Rail) acc. to IEC 60715	
Mounting Position	any	
Recommended Screw Driver	Pozidriv 2	
Accessories Available	Yes	
Connecting Capacity	Busbar 10 / 10 mm ² Flexible with Ferrule 0.75 ... 25 mm ² Flexible 0.75 ... 25 mm ² Flexible 0.75 ... 25 mm ² Rigid 0.75 ... 35 mm ² Stranded 0.75 ... 35 mm ²	
Installation Size	acc. to DIN 43880 3	
Terminal Type	Double Clamp	

Material Compliance

RoHS Information	2CDK400595D2705
RoHS Status	Following EU Directive 2011/65/EU and Amendment 2015/863 July 22, 2019
RoHS Date	20200514
REACH Declaration	9AKK107492A1906
REACH Information	True - contains substances > 0.1 mass percentage
REACH Date	20240821
Conflict Minerals Reporting Template (CMRT)	9AKK108468A3363
SCIP	89318623-ff2d-4ce0-aefe-5d16fac11138 Germany (DE)

Environmental

Ambient Air Temperature	Operation -25 ... +55 °C Storage -40 ... +70 °C
Degree of Protection	IP20 IP40 Enclosure with Cover IP40
Pollution Degree	3
Environmental Conditions	28 cycles with 55 °C / 90-96 % and 25 °C / 95-100 %
Resistance to Vibrations	20 Cycles with Load 0.8 In: 5g 5 ... 150 ... 5 Hz
Resistance to Shock acc. to IEC 60068-2-27	25g 2 shocks 13 ms
Environmental Information	9AKK107680A9140

Technical UL/CSA

Maximum Operating Voltage UL/CSA	480Y / 277 V AC
Interrupting Rating acc. to UL489	(240 V AC) 10 kA (480Y / 277 V AC) 10 kA
Connecting Capacity UL/CSA	Busbar 18-8 AWG Conductor 18-4 AWG

Dimensions

Width in Number of Modular Spacings	4.0
Product Net Width	70 mm
Product Net Height	111 mm
Product Net Depth / Length	69 mm
Product Net Weight	0.5 kg
Pole Net Weight	0.125 kg
Built-In Depth (t ₂)	69 mm

Ordering

Package Level 1 Units	carton 1 piece
Package Level 1 Gross Weight	0.54 kg

Certificates and Declarations

Declaration of Conformity - CE	2CDK400595D2705
Declaration of Conformity - UKCA	9AKK108467A5201

Installation

Instructions and Manuals	2CDC002177D0202
--------------------------	-----------------

Popular Downloads	
Data Sheet, Technical Information	2CDC002177D0202

External Classifications and Standards	
ETIM 8	EC000042 - Miniature circuit breaker (MCB)
ETIM 9	EC000042 - Miniature circuit breaker (MCB)
WEEE Category	5. Small Equipment (No External Dimension More Than 50 cm)
WEEE B2C / B2B	Business To Business
CN8	8536 20 10
UNSPSC	39121603
eClass	V11.0 : 27141901
IDEA Granular Category Code (IGCC)	4899 >> Miniature circuit breaker (MCB) screw-in model
Standards	CSA 22.2 No. 5 IEC/EN 60947-2 UL 489
Certification Agency	CSA EN IEC UL

Accessories				
Identifier	Description	Type	Quantity	Unit Of Measure
2CCA880100R0001	Sensor	CMS-100PS	1	piece
2CCA880101R0001	Sensor	CMS-101PS	1	piece
2CCA880102R0001	Sensor	CMS-102PS	1	piece
2CDS200914R0001	Auxiliary Contact	S2C-H6RU	1	piece
2CDS200924R0001	Signal / Auxiliary Contact	S2C-S6RU	1	piece
2CDS200908R0001	Shunt Trip	S2C-A1U	1	piece
2CDS200908R0002	Shunt Trip	S2C-A2U	1	piece

Categories
Low Voltage Products and Systems → Modular DIN Rail Products → Miniature Circuit Breakers MCBs → Miniature Circuit Breakers MCBs

