



PRODUCT-DETAILS

SU204M-C7

Miniature Circuit Breaker - SU200M - 4P - 7 A - C



General Information	
Extended Product Type	SU204M-C7
Product ID	2CDS274337R0074
EAN	4016779931519
Catalog Description	Miniature Circuit Breaker - SU200M - 4P - 7 A - C
Long Description	SU204M-C7 Miniature Circuit Breaker SU204M-C7 Miniature Circuit Breaker C-Char., 10kA, 7A, 4P

Technical	
Standards	CSA 22.2 No. 5 IEC/EN 60947-2 UL 489
Tripping Characteristic	C
Rated Operational Voltage	acc. to IEC 60898-1 277 V acc. to IEC 60947-2 400 V AC
Rated Insulation Voltage (U _i)	acc. to IEC/EN 60664-1 440 V
Rated Impulse Withstand Voltage (U _{imp})	4 kV at 2000 m 5 kV

)	at Sea Level 6.2 kV
Input Voltage Type	AC/DC
Rated Current (I _n)	7 A
Rated Short-Circuit Capacity	(400 V AC) 11.2 kA
Rated Ultimate Short-Circuit Breaking Capacity (I _{cu})	(400 V AC) 15 kA (400 V) 15 kA
Rated Conditional Short-Circuit Current (I _{nc})	(400 V) 10 kA
Rated Service Short-Circuit Breaking Capacity (I _{cs})	(400 V AC) 11.2 kA
Rated Frequency (f)	50 / 60 Hz DC
Power Loss	6 W at Rated Operating Conditions per Pole 1.5 W
Energy Limiting Class	3
Number of Protected Poles	4
Number of Poles	4P
Overvoltage Category	III
Accessories Available	Yes
Connecting Capacity	Flexible with Ferrule 0.75 ... 25 mm ² Flexible 0.75 ... 25 mm ² Flexible 0.75 ... 25 mm ² Rigid 0.75 ... 35 mm ² Stranded 0.75 ... 35 mm ²
Terminal Type	Double Clamp

Material Compliance

RoHS Information	2CDK400595D2705
RoHS Status	Following EU Directive 2011/65/EU and Amendment 2015/863 July 22, 2019
RoHS Date	20200514
REACH Declaration	9AKK107492A1906
REACH Information	True - contains substances > 0.1 mass percentage
REACH Date	20240821
Conflict Minerals Reporting Template (CMRT)	9AKK108468A3363

Environmental

Ambient Air Temperature	Operation -25 ... +55 °C
Degree of Protection	IP20
Pollution Degree	3
Environmental Information	9AKK107680A9140

Technical UL/CSA

Interrupting Rating acc. to UL489	(240 V AC) 10 kA (480V / 277 V AC) 10 kA
-----------------------------------	---

Dimensions	
Width in Number of Modular Spacings	4.0
Product Net Width	70 mm
Product Net Height	111 mm
Product Net Depth / Length	69 mm
Product Net Weight	0.5 kg
Built-In Depth (t ₂)	69 mm

Ordering	
Package Level 1 Units	carton 2 piece
Package Level 1 Gross Weight	1.012 kg

Certificates and Declarations	
Declaration of Conformity - CE	2CDK400595D2705
Declaration of Conformity - UKCA	9AKK108467A5201
Certification Agency	CSA EN IEC UL

Installation	
Instructions and Manuals	2CDS207104P0001

Popular Downloads	
Data Sheet, Technical Information	2CDC002177D0202

Classifications	
ETIM 8	EC000042 - Miniature circuit breaker (MCB)
ETIM 9	EC000042 - Miniature circuit breaker (MCB)
WEEE Category	5. Small Equipment (No External Dimension More Than 50 cm)
WEEE B2C / B2B	Business To Business
CN8	8536 20 10
UNSPSC	39121603
eClass	V11.0 : 27141901
IDEA Granular Category Code (IGCC)	4899 >> Miniature circuit breaker (MCB) screw-in model

Categories

Low Voltage Products and Systems → Modular DIN Rail Products → Miniature Circuit Breakers MCBs → Miniature Circuit Breakers MCBs

