



PRODUCT-DETAILS

# SU204MR-K13

## Miniature Circuit Breaker - SU200MR - 4P - 13 A - K



| General Information   |                                                                    |
|-----------------------|--------------------------------------------------------------------|
| Extended Product Type | SU204MR-K13                                                        |
| Product ID            | 2CDS274347R0447                                                    |
| EAN                   | 4016779959438                                                      |
| Catalog Description   | Miniature Circuit Breaker - SU200MR - 4P - 13 A - K                |
| Long Description      | SU204MR-K13 MCB K-Char., 10kA, 13A, 4P, RTT UL 489, Ring Cable Lug |

| Technical                                           |                                                                                           |
|-----------------------------------------------------|-------------------------------------------------------------------------------------------|
| Standards                                           | CSA 22.2 No. 5<br>IEC/EN 60947-2<br>UL 489                                                |
| Tripping Characteristic                             | K                                                                                         |
| Rated Operational Voltage                           | acc. to IEC 60898-1 400 V AC<br>acc. to IEC 60898-1 400 V<br>acc. to IEC 60947-2 400 V AC |
| Rated Insulation Voltage (U <sub>i</sub> )          | acc. to IEC/EN 60664-1 440 V                                                              |
| Rated Impulse Withstand Voltage (U <sub>imp</sub> ) | 4 kV<br>at 2000 m 5 kV                                                                    |

|                                                                   |                                                                                                                                                                                                                |
|-------------------------------------------------------------------|----------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------|
| )                                                                 | at Sea Level 6.2 kV                                                                                                                                                                                            |
| Input Voltage Type                                                | AC                                                                                                                                                                                                             |
| Rated Current (I <sub>n</sub> )                                   | 13 A                                                                                                                                                                                                           |
| Rated Short-Circuit Capacity                                      | (230 V AC) 10 kA<br>(400 V AC) 10 kA                                                                                                                                                                           |
| Rated Ultimate Short-Circuit Breaking Capacity (I <sub>cu</sub> ) | (230 V AC) 10 kA<br>(400 V AC) 15 kA<br>(400 V) 6 kA                                                                                                                                                           |
| Rated Conditional Short-Circuit Current (I <sub>nc</sub> )        | (230 V) 10 kA<br>(400 V) 10 kA                                                                                                                                                                                 |
| Rated Service Short-Circuit Breaking Capacity (I <sub>cs</sub> )  | (400 V AC) 11.2 kA                                                                                                                                                                                             |
| Rated Frequency (f)                                               | 50 / 60 Hz                                                                                                                                                                                                     |
| Power Loss                                                        | 9.2 W<br>at Rated Operating Conditions per Pole 2.3 W                                                                                                                                                          |
| Energy Limiting Class                                             | 3                                                                                                                                                                                                              |
| Number of Protected Poles                                         | 4                                                                                                                                                                                                              |
| Number of Poles                                                   | 4P                                                                                                                                                                                                             |
| Overvoltage Category                                              | III                                                                                                                                                                                                            |
| Screw Terminal Type                                               | Ring-Tongue Terminal with Captive Screw                                                                                                                                                                        |
| Options Provided                                                  | Ring tongue                                                                                                                                                                                                    |
| Recommended Screw Driver                                          | Pozidriv 2                                                                                                                                                                                                     |
| Accessories Available                                             | Yes                                                                                                                                                                                                            |
| Connecting Capacity                                               | Flexible with Ferrule 0.75 ... 25 mm <sup>2</sup><br>Flexible 0.75 ... 25 mm <sup>2</sup><br>Flexible 0.75 ... 25 mm <sup>2</sup><br>Rigid 0.75 ... 35 mm <sup>2</sup><br>Stranded 0.75 ... 35 mm <sup>2</sup> |
| Terminal Type                                                     | Ring-Tongue Terminals                                                                                                                                                                                          |

Material Compliance

|                                             |                                                                        |
|---------------------------------------------|------------------------------------------------------------------------|
| RoHS Information                            | 2CDK400616D2703                                                        |
| RoHS Status                                 | Following EU Directive 2011/65/EU and Amendment 2015/863 July 22, 2019 |
| RoHS Date                                   | 20200320                                                               |
| REACH Declaration                           | 9AKK107492A1906                                                        |
| REACH Information                           | True - contains substances > 0.1 mass percentage                       |
| REACH Date                                  | 20240821                                                               |
| Conflict Minerals Reporting Template (CMRT) | 9AKK108468A3363                                                        |

Environmental

|                           |                          |
|---------------------------|--------------------------|
| Ambient Air Temperature   | Operation -25 ... +55 °C |
| Degree of Protection      | IP20                     |
| Pollution Degree          | 3                        |
| Environmental Information | 9AKK107680A9140          |

Technical UL/CSA

|                          |                  |
|--------------------------|------------------|
| Interrupting Rating acc. | (240 V AC) 10 kA |
|--------------------------|------------------|

to UL489

(480V / 277 V AC) 10 kA

| Dimensions                          |         |
|-------------------------------------|---------|
| Width in Number of Modular Spacings | 4.0     |
| Product Net Width                   | 70 mm   |
| Product Net Height                  | 115 mm  |
| Product Net Depth / Length          | 71 mm   |
| Product Net Weight                  | 0.56 kg |
| Built-In Depth (t <sub>2</sub> )    | 69 mm   |

| Ordering                     |                |
|------------------------------|----------------|
| Package Level 1 Units        | carton 2 piece |
| Package Level 1 Gross Weight | 1.17 kg        |

| Certificates and Declarations    |                        |
|----------------------------------|------------------------|
| CSA Certificate                  | 2CDZ405000A0575        |
| Declaration of Conformity - CE   | 2CDK400616D2703        |
| Declaration of Conformity - UKCA | 9AKK108467A5203        |
| UL Certificate                   | 2CDZ405000A0085        |
| Certification Agency             | CSA<br>EN<br>IEC<br>UL |

| Installation             |                 |
|--------------------------|-----------------|
| Instructions and Manuals | 2CDC002184D0202 |

| Popular Downloads                 |                 |
|-----------------------------------|-----------------|
| Data Sheet, Technical Information | 2CDC002184D0202 |

| Classifications                    |                                                            |
|------------------------------------|------------------------------------------------------------|
| ETIM 8                             | EC000042 - Miniature circuit breaker (MCB)                 |
| ETIM 9                             | EC000042 - Miniature circuit breaker (MCB)                 |
| WEEE Category                      | 5. Small Equipment (No External Dimension More Than 50 cm) |
| WEEE B2C / B2B                     | Business To Business                                       |
| CN8                                | 8536 20 10                                                 |
| UNSPSC                             | 39121603                                                   |
| eClass                             | V11.0 : 27141901                                           |
| IDEA Granular Category Code (IGCC) | 4899 >> Miniature circuit breaker (MCB) screw-in model     |

| Accessories     |                            |           |          |                 |
|-----------------|----------------------------|-----------|----------|-----------------|
| Identifier      | Description                | Type      | Quantity | Unit Of Measure |
| 2CCA880100R0001 | Sensor                     | CMS-100PS | 1        | piece           |
| 2CCA880101R0001 | Sensor                     | CMS-101PS | 1        | piece           |
| 2CCA880102R0001 | Sensor                     | CMS-102PS | 1        | piece           |
| 2CDS200914R0001 | Auxiliary Contact          | S2C-H6RU  | 1        | piece           |
| 2CDS200924R0001 | Signal / Auxiliary Contact | S2C-S6RU  | 1        | piece           |
| 2CDS200908R0001 | Shunt Trip                 | S2C-A1U   | 1        | piece           |
| 2CDS200908R0002 | Shunt Trip                 | S2C-A2U   | 1        | piece           |

Categories

Low Voltage Products and Systems → Modular DIN Rail Products → Miniature Circuit Breakers MCBs → Miniature Circuit Breakers MCBs

