



Figure similar

SIEMENS LOW VOLTAGE ES SERIES LOAD CENTER. MAIN LUG WITH 12 1-Inch Spaces ALLOWING MAX 24 CIRCUITS. 1-PHASE 3-WIRE SYSTEM RATED 120/240V(225A) 100KA INTERRUPT. SPECIAL FEATURES: ALUMINUM BUS, GRAY TRIM, NEMA TYPE3R ENCLOSURE FOR OUTDOOR USE. REPLACED BY SNW1224L1225. AVAILABLE 4/1/2020

General technical data

| | |
|------------------------------|-------------|
| configuration of the busbars | 225 A |
| fastening method | Surface |
| phase number | 1 |
| suitability for operation | Residential |

Electricity

| | |
|--|-------|
| ampacity | 225 A |
| ampacity minimum | 225 A |
| voltage between phase and Ground (GND) rated value | 120 V |
| voltage between phase and phase rated value | 240 V |

Switching capacity

| | |
|--|---------|
| switching capacity current according to EN 60898 rated value | 22000 A |
|--|---------|

Model

| | |
|------------------------|--------------|
| product brand name | Siemens |
| product sub brand name | Load Centers |

Mechanical Design

| | |
|--|----|
| number of modular width units for installation width | 12 |
|--|----|

last modified:

6/18/2021 

