




PRODUCT-DETAILS

SZ-KS2/56

Terminal 1 phase



General Information	
Extended Product Type	SZ-KS2/56
Product ID	GJI2322322R0004
EAN	4012233598205
Catalog Description	Terminal 1 phase
Long Description	KS 2/56 UNIVERSAL COMB-BUSBAR

Technical	
Rated Operational Voltage	400 V Maximum 400 V
Voltage Protection Level (Up)	4.5 kV
Rated Short-time Withstand Current Low Voltage (I _{cw})	25 kA
Rated Uninterrupted Current (I _u)	100 A
Pitch	17.5
Number of Poles	56P

Number of Phases	1
Number of Mountable Devices	56
Accessory Type	Busbar
Connection Type	Pin
Rated Cross-Section	24 mm ²

Material Compliance

RoHS Information	9AKK108468A1264
RoHS Status	Following EU Directive 2011/65/EU and Amendment 2015/863 July 22, 2019
RoHS Date	20230517
REACH Declaration	9AKK107492A1906
REACH Information	False - does not contain substances > 0.1 mass percentage
REACH Date	20240821
Conflict Minerals Reporting Template (CMRT)	9AKK108468A3363

Dimensions

Product Net Depth / Length	988 mm
Product Net Weight	0.135 kg

Ordering

Package Level 1 Units	50 piece
Package Level 1 Gross Weight	7.2 kg
E-Number (Sweden)	2102661

Certificates and Declarations

Declaration of Conformity - CE	9AKK108469A0841
Declaration of Conformity - UKCA	9AKK108469A0914

Installation

Instructions and Manuals	No document needed
--------------------------	--------------------

Popular Downloads

Data Sheet, Technical Information	No document needed
-----------------------------------	--------------------

Classifications

ETIM 8	EC000215 - Phase busbar
--------	-------------------------

ETIM 9	EC000215 - Phase busbar
WEEE Category	4. Large Equipment (Any External Dimension More Than 50 cm)
WEEE B2C / B2B	Business To Business
CN8	8538 90 99
UNSPSC	39121117
eClass	V11.0 : 27371306
IDEA Granular Category Code (IGCC)	4378 >> Phase busbar

Categories

Low Voltage Products and Systems → Modular DIN Rail Products → Miniature Circuit Breakers MCBs → Miniature Circuit Breakers MCBs Accessories → Busbars and Accessories (IEC Range)

