




PRODUCT-DETAILS

SZ-PSB64N

Terminal 3 phase



General Information	
Extended Product Type	SZ-PSB64N
Product ID	GHV0360874R0042
EAN	4012233550500
Catalog Description	Terminal 3 phase
Long Description	SZ-PSB 64N BUSBAR FOR SUR. ARRST.

Technical	
Rated Operational Voltage	690 V Maximum 690 V
Voltage Protection Level (Up)	4.5 kV
Rated Short-time Withstand Current Low Voltage (I _{cw})	25 kA
Rated Uninterrupted Current (I _u)	80 A
Pitch	44698.0
Number of Poles	60P

Number of Phases	3
Number of Mountable Devices	15
Accessory Type	Busbar
Connection Type	Pin
Rated Cross-Section	16 mm²

Material Compliance

RoHS Information	9AKK108468A1264
RoHS Status	Following EU Directive 2011/65/EU and Amendment 2015/863 July 22, 2019
RoHS Date	20230517
REACH Declaration	9AKK107492A1906
REACH Information	False - does not contain substances > 0.1 mass percentage
REACH Date	20240821
Conflict Minerals Reporting Template (CMRT)	9AKK108468A3363

Dimensions

Product Net Width	21.3 mm
Product Net Height	31 mm
Product Net Depth / Length	1060 mm
Product Net Weight	0.86 kg

Ordering

Package Level 1 Units	10 piece
Package Level 1 Gross Weight	9 kg
E-Number (Norway)	1629678

Certificates and Declarations

Declaration of Conformity - CE	9AKK108469A0841
Declaration of Conformity - UKCA	9AKK108469A0914

Installation

Instructions and Manuals	No document needed
--------------------------	--------------------

Popular Downloads

Data Sheet, Technical Information	No document needed
-----------------------------------	--------------------

Classifications		
ETIM 8	EC000215 - Phase busbar	
ETIM 9	EC000215 - Phase busbar	
WEEE Category	4. Large Equipment (Any External Dimension More Than 50 cm)	
WEEE B2C / B2B	Business To Business	
CN8	8538 90 99	
UNSPSC	39121117	
eClass	V11.0 : 27371306	
IDEA Granular Category Code (IGCC)	4378 >> Phase busbar	
Object Classification Code	W	

Categories

Low Voltage Products and Systems → Modular DIN Rail Products → Miniature Circuit Breakers MCBs → Miniature Circuit Breakers MCBs Accessories → Busbars

