

PRODUCT-DETAILS

T4N 250 UL/CSA PR222DS/P-LSI 250 3p F F

T4N 250 UL/CSA PR222DS/P-LSI 250 3p F F



General Information

Extended Product Type	T4N 250 UL/CSA PR222DS/P-LSI 250 3p F F
Product ID	1SDA055416R1
EAN	8015644567170
Catalog Description	T4N 250 UL/CSA PR222DS/P-LSI 250 3p F F
Long Description	C.BREAKER TMAX T4N 250 UL/CSA FIXED THREE-POLE WITH FRONT TERMINALS AND SOLID-STATE RELEASE IN AC PR222DS/P-LSI R 250

Ordering

EAN	8015644567170
Minimum Order Quantity	1 piece
Customs Tariff Number	85362090
Order Code US and Canada	T4N250CW

Dimensions

Product Net Weight	1 kg
--------------------	------

Container Information

Package Level 1 EAN	8015644567170
---------------------	---------------

Additional Information

Mechanical Durability	20000 cycle
Number of Poles	3
Power Loss	at Rated Operating Conditions per Pole 13.7 W
Product Main Type	SACE Tmax T
Product Name	Moulded Case Circuit Breaker
Product Type	CB
Rated Current (I_n)	250 A
Rated Operational Voltage	600 V AC 600 V DC
Rated Ultimate Short-Circuit Breaking Capacity (I_{cu})	(240 V AC) 65 kA (480 V AC) 25 kA (600 V AC) 18 kA (500 V DC) 2 Poles in Series 25 kA (600 V DC) 3 Poles in Series 16 kA
Rated Uninterrupted Current (I_u)	250 A
Release	PR222DS/P-LSI
Release Type	EL
Short-Circuit Performance Level	N
Standards	UL 489 CSA C22.2
Sub-type	T4
Terminal Connection Type	Fixed Circuit-Breakers Front
Test Voltage Max (U_{test})	3500 V
Version	F

Certificates and Declarations (Document Number)

Data Sheet, Technical Information	9AKK105713A5947
Declaration of Conformity - CE	1SDL000165R0004
Instructions and Manuals	1SDC210023D0201

Classifications

WEEE Category	5. Small Equipment (No External Dimension More Than 50 cm)
---------------	--

Categories

Low Voltage Products and Systems → Circuit Breakers → Moulded Case Circuit Breakers → Tmax T

