



Molded Case Circuit Breakers T&B Catalog Number:

| UPC | Number: |
|-------|----------|
| Statu | IS: |
| Desc | ription: |

T4N250E5W 8015644618322 Active

3 pole, 250 amps rated at 600V AC, Tmax molded case circuit breaker with an electronic trip device with a magnetic interrupt (MCP) trip device and 25kA at 480V AC interrupt current rating **Features**

| | Short circuit protection is provided by an adjustable |
|-----------------------|---|
| | instantaneous only, magnetic trip unit (MCP) |
| | Advanced contact design and arcing chambers pro- |
| | vide the latest in fault current protection |
| | Adjustable trip point from 250 to 2500A |
| Application | |
| | For motor control applications (MCP) |
| | Can be installed in either the horizontal or vertical |
| | planes |
| | Suitable for reverse feed applications |
| General | |
| Тгір Туре | Electronic with magnetic interrupt (MCP) |
| Number of Poles | 3 |
| Series | T4 |
| Approvals | |
| UL Class | UL 489 |
| Dimension Information | |
| H x W x D (inches) | 8.07 x 4.13 x 4.07 |
| Specifications | |
| Rated Current (Amps) | 250 |
| Rated Voltage AC | 600 |
| Interrupt Rating | 25kA at 480V AC |
| Packaging | |
| Package in Units | 1 |
| T&B Sold in UOM | Each |
| T&B Weight Per UOM | 8.43 lbs. Each |
| 5 | |