

PRODUCT-DETAILS

# T5L400 UL TMA 400-2000..4000 4p FF N100%

T5L400 UL TMA 400-2000..4000 4p FF N100%



## General Information

Extended Product Type	T5L400 UL TMA 400-2000..4000 4p FF N100%
Product ID	1SDA060645R1
EAN	8015644631604
Catalog Description	T5L400 UL TMA 400-2000..4000 4p FF N100%
Long Description	C.BREAKER TMAX T5L 400 UL/CSA FIXED FOUR-POLE WITH FRONT TERMINALS AND THERMOMAGNETIC RELEASE TMA R 400 I3=2000...4000 A FULLY RATED NEUTRAL

## Ordering

EAN	8015644631604
Minimum Order Quantity	1 piece
Customs Tariff Number	85362090
Order Code US and Canada	T5L400TW-4

## Dimensions

Product Net Width	186 mm
Product Net Height	205 mm
Product Net Depth / Length	103.5 mm
Product Net Weight	4.15 kg

---

**Container Information**


---

Package Level 1 EAN

8015644631604

---

**Environmental**


---

RoHS Status

Following EU Directive 2011/65/EU and Amendment 2015/863 July 22, 2019

---

**Technical UL/CSA**


---

Interrupting Rating acc.  
to UL489(240 V AC) 200 kA  
(480 V AC) 100 kA  
(600 V AC) 65 kA  
(500 V DC) 2 Poles in Series 65 kA  
(600 V DC) 3 Poles in Series 50 kA

---

**Additional Information**


---

Mechanical Durability	20000 cycle 120 cycles per hour
Number of Poles	4
Power Loss	at Rated Operating Conditions per Pole 19.5 W
Product Main Type	SACE Tmax T
Product Name	Moulded Case Circuit Breaker
Product Type	CB
Rated Current (I <sub>n</sub> )	Main Circuit 400 A
Rated Impulse Withstand Voltage (U <sub>imp</sub> )	8 kV
Rated Insulation Voltage (U <sub>i</sub> )	1000 V
Rated Operational Voltage	600 V AC 600 V DC
Rated Ultimate Short- Circuit Breaking Capacity (I <sub>cu</sub> )	(240 V AC) 200 kA (480 V AC) 100 kA (600 V AC) 65 kA (500 V DC) 2 Poles in Series 65 kA (600 V DC) 3 Poles in Series 50 kA
Rated Uninterrupted Current (I <sub>u</sub> )	400 A
Release	TMA
Release Type	TM
Short-Circuit Performance Level	L
Standards	UL
Sub-type	T5
Suitable For	T5
Suitable for Product Class	Moulded Case Circuit Breakers
Terminal Connection Type	Fixed Circuit-Breakers Front
Test Voltage Max (U <sub>test</sub> )	3500 V
Version	F

---

**Certificates and Declarations (Document Number)**


---

Data Sheet, Technical Information	9AKK105713A5947
Declaration of Conformity - CE	9AKK106713A5539

Environmental Information	9AKK10103A1056
GL Certificate	1SDL000163R0062
Instructions and Manuals	1SDC210023D0201
REACH Declaration	9AKK108466A1425
RoHS Information	9AKK108466A1424

---

## Classifications

ETIM 6	EC000228 - Power circuit-breaker for trafo/generator/installation prot.
ETIM 7	EC000228 - Power circuit-breaker for trafo/generator/installation protection
ETIM 8	EC000228 - Power circuit-breaker for trafo/generator/installation protection
WEEE Category	5. Small Equipment (No External Dimension More Than 50 cm)

---

## Categories

Low Voltage Products and Systems → Circuit Breakers → Moulded Case Circuit Breakers → Tmax T

