



PRODUCT-DETAILS

T5N 400 UL/CSA PR221DS-LS/I 400 4p F F

T5N 400 UL/CSA PR221DS-LS/I 400 4p F F



General Information	
Extended Product Type	T5N 400 UL/CSA PR221DS-LS/I 400 4p F F
Product ID	1SDA060116R1
EAN	8015644625627
Catalog Description	T5N 400 UL/CSA PR221DS-LS/I 400 4p F F
Long Description	C.BREAKER TMAX T5N 400 UL/CSA FIXED FOUR-POLE WITH FRONT TERMINALS AND SOLID-STATE RELEASE IN AC PR221DS-LS/I R 400

Material Compliance	
REACH Declaration	9AKK108466A1425
RoHS Information	9AKK108466A1424
RoHS Status	Following EU Directive 2011/65/EU and Amendment 2015/863 July 22, 2019
Conflict Minerals Reporting Template (CMRT)	9AKK108467A5658
Toxic Substances Control Act - TSCA	9AKK108467A8326

Environmental

Environmental Information	9AKK10103A1056 9AKK108467A6707
---------------------------	-----------------------------------

Ordering

Order Code US and Canada	T5N400BW-4
EAN	8015644625627
Minimum Order Quantity	1 piece
Customs Tariff Number	85362090

Dimensions

Product Net Width	186 mm
Product Net Height	205 mm
Product Net Depth / Length	103.5 mm
Product Net Weight	6.2 kg

Container Information

Package Level 1 EAN	8015644625627
---------------------	---------------

Additional Information

Product Main Type	SACE Tmax T
Product Name	Moulded Case Circuit Breaker
Product Type	Automatic Circuit Breaker
Suitable For	T5
Suitable for Product Class	Moulded Case Circuit Breakers
Version	F

Technical

Mechanical Durability	20000 cycle 120 cycles per hour
Number of Poles	4P
Power Loss	at Rated Operating Conditions per Pole 16.5 W
Rated Current (I_n)	400 A
Rated Impulse Withstand Voltage (U_{imp})	8 kV
Rated Insulation Voltage (U_i)	1000 V
Rated Operational Voltage	600 V AC
Rated Uninterrupted Current (I_u)	400 A
Release	PR221DS-LS/I
Release Type	EL
Short-Circuit	N

Performance Level

Standards	UL
Sub-type	T5
Terminal Connection Type	Fixed Circuit-Breakers Front
Test Voltage Max (U _{test})	3500 V

Technical UL/CSA

Interrupting Rating acc. to UL489	(240 V AC) 65 kA (480 V AC) 25 kA (600 V AC) 18 kA
-----------------------------------	--

Certificates and Declarations

Data Sheet, Technical Information	9AKK105713A5947
Declaration of Conformity - CE	9AKK106713A5539
Instructions and Manuals	1SDC210023D0201

External Classifications and Standards

ETIM 8	EC000228 - Power circuit-breaker for trafo/generator/installation protection
ETIM 9	EC000228 - Power circuit-breaker for trafo/generator/installation protection
IDEA Granular Category Code (IGCC)	4934 >> 4 Pole Non-Interchangeable Trip Electronic Circuit Breakers
UNSPSC	39121616
WEEE Category	5. Small Equipment (No External Dimension More Than 50 cm)
eClass	V11.1 : 27370409

Categories

Low Voltage Products and Systems → Circuit Breakers → Moulded Case Circuit Breakers → Tmax T

