



AL..RT and TAL..RT 4-pole Contactors

d.c. Operated



TAL 9-40-00RT

1SBC5 9085 5F0304



TAL 26-40-00RT

1SBC5 9092 6F0304

Ordering Details

IEC	UL/CSA	Auxiliary contacts fitted	Type	Order code	Weight kg
AC-1 Rated current $\theta \leq 40^\circ\text{C}$	General use rating 600 V		state coil voltage (see table below)	state coil voltage code (see table below)	Pack ^{ing} 1 piece
A	A				

4 N.O. Main Poles - 3 W and 3.5 W consumption

25	21	--	AL 9-40-00RT	1SBL 143 210 R 00	0.520
30	30	--	AL 16-40-00RT	1SBL 183 210 R 00	0.520
45	40	--	AL 26-40-00RT	1SBL 243 210 R 00	0.750

2 N.O. + 2 N.C. Main Poles - 3 W and 3.5 W consumption

25	21	--	AL 9-22-00RT	1SBL 143 510 R 00	0.520
30	30	--	AL 16-22-00RT	1SBL 183 510 R 00	0.520
45	40	--	AL 26-22-00RT	1SBL 243 510 R 00	0.750

4 N.O. Main Poles - Large coil voltage range

25	21	--	TAL 9-40-00RT	1SBL 143 260 R 00	0.520
30	30	--	TAL 16-40-00RT	1SBL 183 260 R 00	0.520
45	40	--	TAL 26-40-00RT	1SBL 243 260 R 00	0.750

2 N.O. + 2 N.C. Main Poles - Large coil voltage range

25	21	--	TAL 9-22-00RT	1SBL 143 560 R 00	0.520
30	30	--	TAL 16-22-00RT	1SBL 183 560 R 00	0.520
45	40	--	TAL 26-22-00RT	1SBL 243 560 R 00	0.750

Coil voltages and codes for AL..RT

Voltage - U_c V d.c.	Code
12	8 0
24	8 1
42	8 2
48	8 3
60	8 4
75	8 5
110	8 6
125	8 7
220	8 8
240	8 9

Coil voltages and codes for TAL..RT

Voltage - U_c V d.c.	Code
17 ... 32	5 1
25 ... 45	5 2
36 ... 65	5 4
42 ... 78	5 8
50 ... 90	5 5
77 ... 143	6 2
90 ... 150	6 6
152 ... 264	6 8



Voltage tolerances (-15% and +10%) included in the U_c min. and U_c max. values for the TAL..RT contactors.