



TAL..RT 3-pole Contactors

d.c. Operated



Ordering Details


3-pole Contactors - Large coil voltage range

IEC		UL/CSA		Auxiliary contacts fitted		Type	Order code	Weight kg
AC-3 Rated power	AC-1 Rated current	3-Phase motor rating	General use rating	1 st stack	2 nd stack			
400 V	$\theta \leq 40^{\circ}\text{C}$	480 V	600 V			state coil voltage (see table below)	state coil voltage code (see table below)	Pack ^{ing} 1 piece
kW	A	hp	A					
4	25	5	21	1 –	–	TAL 9-30-10RT	1SBL 143 060 R 10	0.520
				– 1	–	TAL 9-30-01RT	1SBL 143 060 R 01	0.520
5.5	27	7.5	25	1 –	–	TAL 12-30-10RT	1SBL 163 060 R 10	0.520
				– 1	–	TAL 12-30-01RT	1SBL 163 060 R 01	0.520
7.5	30	10	30	1 –	–	TAL 16-30-10RT	1SBL 183 060 R 10	0.520
				– 1	–	TAL 16-30-01RT	1SBL 183 060 R 01	0.520
11	45	20	40	1 –	–	TAL 26-30-10RT	1SBL 243 060 R 10	0.750
				– 1	–	TAL 26-30-01RT	1SBL 243 060 R 01	0.750
15	50	25	50	1 –	–	TAL 30-30-10RT	1SBL 283 060 R 10	0.850
				– 1	–	TAL 30-30-01RT	1SBL 283 060 R 01	0.850
18.5	60	30	60	1 –	–	TAL 40-30-10RT	1SBL 323 060 R 10	0.850
				– 1	–	TAL 40-30-01RT	1SBL 323 060 R 01	0.850

Coil voltages and codes

Voltage - U_c V d.c.	Code
17 ... 32	5 1
25 ... 45	5 2
36 ... 65	5 4
42 ... 78	5 8
50 ... 90	5 5
77 ... 143	6 2
90 ... 150	6 6
152 ... 264	6 8


Voltage tolerances (-15% and +10%) included in the U_c min. and U_c max. values for the TAL..RT contactors.



TAL 9-30-10RT



TAL 26-30-10RT



TAL 30-30-10RT