

TCSMCN1M1F1

Radio frequency identification XG, Modbus shielded cable, M12 male connector, M12 female connector, IP67, 1 m



Main

Range of product	Telemecanique Radio frequency identification XG
Accessory / separate part categor	Connection accessories
Accessory / separate part type	Connecting cable
Accessory / separate part designation	Modbus shielded connecting cable
Accessory / separate part destination	Tap-off box Compact station
Cable length	1 m

Complementary

Electrical connection	1 female connector M12 straight A coding 1 male connector M12 straight A coding
Colour	Black
Net weight	0.08 kg

Environment

IP degree of protection	IP67
-------------------------	------

Packing Units

Unit Type of Package 1	PCE
Number of Units in Package 1	1
Package 1 Height	2.000 cm
Package 1 Width	15.000 cm
Package 1 Length	16.000 cm
Package 1 Weight	95.000 g
Unit Type of Package 2	S02
Number of Units in Package 2	30
Package 2 Height	15 cm
Package 2 Width	30 cm
Package 2 Length	40 cm
Package 2 Weight	3.170 kg

Offer Sustainability

Toxic heavy metal free	Yes
California proposition 65	WARNING: This product can expose you to chemicals including: Diisononyl phthalate (DINP), which is known to the State of California to cause cancer, and Di-isodecyl phthalate (DIDP), which is known to the State of California to cause birth defects or other reproductive harm. For more information go to www.P65Warnings.ca.gov
For all Reach Rohs enquiries contact us at	sustainability@tesensors.com

Contractual warranty

Warranty	18 months
----------	-----------