TELE L-1 1/3



PRODUCT-DETAILS

## **TELE L-1**Shunt Trip



General Information	
Extended Product Type	TELE L-1
Product ID	4TQA670903R0000
EAN	5411815227974
Catalog Description	Shunt Trip
Long Description	The Tele L allows to remotely switch off any MCB, RCCB or RCBO by means of push-buttons or any other automatic management processor. A built-in contact in series with the coil prevents burn- out damage if the voltage remains.

Technical	
Rated Operational Voltage	24/60 V AC
Rated Frequency (f)	50 / 60 Hz
Terminal Type	Screw Terminals

## **Material Compliance**

2/3 TELE L-1

RoHS Status	Following EU Directive 2011/65/EU
Conflict Minerals Reporting Template (CMRT)	9AKK108468A3363
SCIP	c08dab4d-ae44-48e7-a775-4f7b9378c726 Poland (PL)

Dimensions	
Width in Number of Modular Spacings	1
Product Net Width	0.018 m
Product Net Height	0.086 m
Product Net Depth / Length	0.076 m
Product Net Weight	0.09 kg
Dimension Diagram	No document available

Ordering	
Package Level 1 Units	box 1 piece
Package Level 1 Gross Weight	0.091 kg

Certificates and Declarations	
Declaration of	No declaration needed
Conformity - CE	

Installation	
Instructions and Manuals	No document needed
Wiring Diagram	No document needed

Popular Downloads	
Data Sheet, Technical	No document needed
Information	

Classifications	
ETIM 8	EC001023 - Shunt release (for power circuit breaker)
ETIM 9	EC001023 - Shunt release (for power circuit breaker)
WEEE Category	5. Small Equipment (No External Dimension More Than 50 cm)
WEEE B2C / B2B	Business To Business
CN8	85365080
eClass	V11.0 : 27370418
Object Classification	Q
Code	

TELE L-1 3/3

## Categories

 $Low\ Voltage\ Products\ and\ Systems \rightarrow Modular\ DIN\ Rail\ Products \rightarrow AEG \rightarrow Busbars\ and\ Accessories$ 









360