Product data sheet

Specifications





logic controller, Modicon M241, 40 IO, relay, Ethernet

TM241CE40R

Product availability: Stock - Normally stocked in distribution facility

Price*: 569.00 USD

Main

Range Of Product	Modicon M241
Product Or Component Type	Logic controller
[Us] Rated Supply Voltage	100240 V AC
Discrete Input Number	24, discrete input 8 fast input IEC 61131-2 Type 1
Discrete Output Type	Relay Transistor
Discrete Output Number	4 transistor 4 fast output 12 relay
Discrete Output Voltage	5125 V DC relay output 5250 V AC relay output 24 V DC transistor output
Discrete Output Current	0.1 A fast output (PTO mode) TR0TR3) 2 A relay output Q4Q15) 0.5 A transistor output TR0TR3)

Complementary

Discrete I/O Number	40
Maximum Number Of I/O Expansion Module	7 (local I/O-Architecture) 14 (remote I/O-Architecture)
Supply Voltage Limits	85264 V
Network Frequency	50/60 Hz
Discrete Input Logic	Sink or source
Discrete Input Voltage	24 V
Discrete Input Voltage Type	DC
Voltage State 1 Guaranteed	>= 15 V input
Voltage State 0 Guaranteed	<= 5 V input
Discrete Input Current	7 mA input
Input Impedance	4.7 kOhm input
Response Time	50 μs turn-on, I0I15 input
Configurable Filtering Time	1 µs fast input
Discrete Output Logic	Positive logic (source)
Output Voltage Limits	125 V DC relay output 30 V DC transistor output 277 V AC relay output

Price is "List Price" and may be subject to a trade discount – check with your local distributor or retailer for actual price.

Maximum Output Frequency	1 kHz transistor output
	20 kHz fast output (PWM mode)
	100 kHz fast output (PLS mode)
Accuracy	+/- 0.1 % 0.020.1 kHz fast output
	+/- 1 % 0.11 kHz fast output
Protection Type	Short-circuit protection transistor output
	Short-circuit and overload protection with automatic reset transistor output
	Reverse polarity protection transistor output
	Without protection relay output
Reset Time	10 ms automatic reset output
	12 s automatic reset fast output
Memory Capacity	64 MB system memory RAM
Data Backed Up	128 MB built-in flash memory backup of user programs
Data Storage Equipment	<= 16 GB SD card optional)
Battery Type	BR2032 lithium non-rechargeable 4 year(s)
Backup Time	2 years 77 °F (25 °C)
Execution Time For 1 Kinstruction	0.3 ms event and periodic task
	0.7 ms other instruction
Application Structure	4 cyclic master tasks
	8 event tasks
	8 external event tasks
	3 cyclic master tasks + 1 freewheeling task
Realtime Clock	With
Clock Drift	<= 60 s/month 77 °F (25 °C)
Positioning Functions	PTO 4 100 kHz)
Counting Input Number	4 fast input (HSC mode) 200 kHz
	14 standard input 1 kHz
Control Signal Type	A/B 100 kHz fast input (HSC mode)
	Pulse/direction 200 kHz fast input (HSC mode)
	Single phase 200 kHz fast input (HSC mode)
Integrated Connection Type	Non isolated serial link serial 1 RJ45 RS232/RS485
	Non isolated serial link serial 2 removable screw terminal block RS485
	USB port mini B USB 2.0
	Ethernet RJ45
Supply	Serial 1)serial link supply 5 V, <200 mA
Transmission Rate	1.2115.2 kbit/s (115.2 kbit/s by default) 49.21 ft (15 m) RS485
	1.2115.2 kbit/s (115.2 kbit/s by default) 9.84 ft (3 m) RS232
	480 Mbit/s 9.84 ft (3 m) USB
	10/100 Mbit/s Ethernet
Communication Port Protocol	Non isolated serial link Modbus master/slave
Port Ethernet	10BASE-T/100BASE-TX - 1 copper cable

Ethernet Services	FDR DHCP server via TM4 Ethernet switch network module DHCP client embedded Ethernet port SMS notifications
	Updating firmware SNMP client/server
	Programming NGVL
	Monitoring IEC VAR ACCESS
	FTP client/server Downloading
	SQL client Modbus TCP client I/O scanner
	Ethernet/IP originator I/O scanner embedded Ethernet port
	Ethernet/IP target, Modbus TCP server and Modbus TCP slave Send and receive email from the controller based on TCP/UDP library
	Web server (WebVisu & XWeb system) OPC UA server
	DNS client
Local Signalling	for PWR 1 LED (green) for RUN 1 LED (green)
	for module error (ERR) 1 LED (red)
	for I/O error (I/O) 1 LED (red) for SD card access (SD) 1 LED (green)
	for BAT 1 LED (red) for SL1 1 LED (green)
	for SL2 1 LED (green) for bus fault on TM4 (TM4) 1 LED (red)
	for I/O state 1 LED per channel (green)
Florida d Companies	for Ethernet port activity 1 LED (green)
Electrical Connection	removable screw terminal block for inputs and outputs pitch 5.08 mm) removable screw terminal block for connecting the 24 V DC power supply pitch 5.08 mm)
Maximum Cable Distance Between Devices	Unshielded cable <164.04 ft (50 m) input Shielded cable <32.81 ft (10 m) fast input
	Unshielded cable <164.04 ft (50 m) output Shielded cable <9.84 ft (3 m) fast output
Insulation	. , , ,
Insulation	Between supply and internal logic 500 V AC Non-insulated between supply and ground
Marking	CE
Sensor Power Supply	24 V DC 400 mA supplied by the controller
Surge Withstand	2 kV power lines (AC) common mode IEC 61000-4-5 2 kV relay output common mode IEC 61000-4-5
	1 kV shielded cable common mode IEC 61000-4-5
	1 kV power lines (AC) differential mode IEC 61000-4-5 1 kV relay output differential mode IEC 61000-4-5
	1 kV input common mode IEC 61000-4-5 1 kV transistor output common mode IEC 61000-4-5
Web Services	Web server
Maximum Number Of	8 Modbus server
Connections	8 SoMachine protocol 10 web server
	4 FTP server 16 Ethernet/IP target
	8 Modbus client
Number Of Server Device(S)	64 Modbus TCP 16 EtherNet/IP
Cycle Time	10 ms 16 EtherNet/IP 64 ms 64 Modbus TCP
Mounting Support	Top hat type TH35-15 rail IEC 60715
	Top hat type TH35-7.5 rail IEC 60715 plate or panel with fixing kit
Height	3.54 in (90 mm)
Depth	3.74 in (95 mm)

Width	7.48 in (190 mm)
Net Weight	1.37 lb(US) (0.62 kg)
Environment	
Standards	ANSI/ISA 12-12-01 CSA C22.2 No 142 CSA C22.2 No 213 IEC 61131-2:2007 Marine specification (LR, ABS, DNV, GL) UL 508
Product Certifications	RCM cULus CE UKCA DNV-GL ABS LR
Resistance To Electrostatic Discharge	8 kV in air IEC 61000-4-2 4 kV on contact IEC 61000-4-2
Resistance To Electromagnetic Fields	9.14 V/m (10 V/m) 80 MHz1 GHz IEC 61000-4-3 2.74 V/m (3 V/m) 1.4 GHz2 GHz IEC 61000-4-3 0.91 V/m (1 V/m) 2 GHz3 GHz IEC 61000-4-3
Resistance To Fast Transients	2 kV IEC 61000-4-4 power lines) 2 kV IEC 61000-4-4 relay output) 1 kV IEC 61000-4-4 Ethernet line) 1 kV IEC 61000-4-4 serial link) 1 kV IEC 61000-4-4 input) 1 kV IEC 61000-4-4 transistor output)
Resistance To Conducted Disturbances	10 V 0.1580 MHz IEC 61000-4-6 3 V 0.180 MHz Marine specification (LR, ABS, DNV, GL) 10 V spot frequency (2, 3, 4, 6.2, 8.2, 12.6, 16.5, 18.8, 22, 25 MHz) Marine specification (LR, ABS, DNV, GL)
Electromagnetic Emission	Conducted emissions 12069 dBµV/m QP power lines)10150 kHz IEC 55011 Conducted emissions 63 dBµV/m QP power lines)1.530 MHz IEC 55011 Conducted emissions 79 dBµV/m QP/66 dBµV/m AV power lines)0.150.5 MHz IEC 55011 Conducted emissions 73 dBµV/m QP/60 dBµV/m AV power lines)0.5300 MHz IEC 55011 Radiated emissions 40 dBµV/m QP class A 10 m)30230 MHz IEC 55011 Conducted emissions 7963 dBµV/m QP power lines)1501500 kHz IEC 55011 Radiated emissions 47 dBµV/m QP class A 10 m)2301000 MHz IEC 55011
Immunity To Microbreaks	10 ms
Ambient Air Temperature For Operation	14122 °F (-1050 °C) vertical installation) 14131 °F (-1055 °C) horizontal installation)
Ambient Air Temperature For Storage	-13158 °F (-2570 °C)
Relative Humidity	1095 %, without condensation in operation) 1095 %, without condensation in storage)
Ip Degree Of Protection	IP20 with protective cover in place
Pollution Degree	2
Operating Altitude	06561.68 ft (02000 m)
Storage Altitude	0.009842.52 ft (03000 m)
Vibration Resistance	3.5 mm 58.4 Hz symmetrical rail 3 gn 8.4150 Hz symmetrical rail 3.5 mm 58.4 Hz panel mounting 3 gn 8.4150 Hz panel mounting
Shock Resistance	15 gn 11 ms

Ordering and shipping details

Category	US10MSX22533
Discount Schedule	OMSX
Gtin	3606480648847
Returnability	Yes
Country Of Origin	ID

Packing Units

. acimig cinic	
Unit Type Of Package 1	PCE
Number Of Units In Package 1	1
Package 1 Height	5.04 in (12.8 cm)
Package 1 Width	8.90 in (22.6 cm)
Package 1 Length	4.53 in (11.5 cm)
Package 1 Weight	32.91 oz (933.0 g)
Unit Type Of Package 2	S03
Number Of Units In Package 2	6
Package 2 Height	11.81 in (30 cm)
Package 2 Width	11.81 in (30 cm)
Package 2 Length	15.75 in (40 cm)
Package 2 Weight	12.85 lb(US) (5.827 kg)
Unit Type Of Package 3	P06
Number Of Units In Package 3	48
Package 3 Height	29.53 in (75.0 cm)
Package 3 Width	15.75 in (40.0 cm)
Package 3 Length	31.50 in (80.0 cm)
Package 3 Weight	132.28 lb(US) (60 kg)

Sustainability Green Premium

Green PremiumTM label is Schneider Electric's commitment to delivering products with best-inclass environmental performance. Green Premium promises compliance with the latest regulations, transparency on environmental impacts, as well as circular and low-CO₂ products.

Guide to assessing product sustainability is a white paper that clarifies global eco-label standards and how to interpret environmental declarations.

Learn more about Green Premium >

Guide to assess a product's sustainability >





Transparency RoHS/REACh

Well-being performance

Ø	Mercury Free	
⊘	Rohs Exemption Information	Yes
⊘	Pvc Free	

Certifications & Standards


Reach Regulation	REACh Declaration
Eu Rohs Directive	Pro-active compliance (Product out of EU RoHS legal scope)
China Rohs Regulation	China RoHS declaration
Environmental Disclosure	Product Environmental Profile
Weee	The product must be disposed on European Union markets following specific waste collection and never end up in rubbish bins.
Circularity Profile	End of Life Information
California Proposition 65	WARNING: This product can expose you to chemicals including: Lead and lead compounds, which is known to the State of California to cause cancer and birth defects or other reproductive harm. For more information go to www.P65Warnings.ca.gov


Product data sheet

TM241CE40R

Dimensions Drawings

Dimensions







Product data sheet

TM241CE40R


Mounting and Clearance

Clearance






Mounting Position




Acceptable Mounting




NOTE: Expansion modules must be mounted above the logic controller.

Incorrect Mounting



Direct Mounting On a Panel Surface


Mounting Hole Layout



Connections and Schema

Digital Inputs


Wiring Diagram (Positive Logic)



(*): Type T fuse

(1): The COM0, COM1 and COM2 terminals are not connected internally.

Wiring Diagram (Negative Logic)




(*): Type T fuse

(1): The COM0, COM1 and COM2 terminals are not connected internally.

Fast Transistor Outputs


Wiring Diagram



(*): 2 A fast-blow fuse


Relay Outputs

Wiring Diagram




- (*): Type T fuse
- (1): The terminals COM1 to COM6 are not connected internally.
- (2): To improve the life time of the contacts, and to protect from potential inductive load damage, you must connect a free wheeling diode in parallel to each inductive DC load or an RC snubber in parallel of each inductive AC load

USB Mini-B Connection



Ethernet Connection to a PC



Jun 3, 2024