



## Molded Case Switches T&B Catalog Number:

UPC Number: Status: Description: TS3H225DW 804325431811 Active

3 pole, 225 amps rated at 600V AC, Tmax molded case switch with magnetic only trip device and 50kA at 480V AC interrupt current rating **Features** 

|                       | Short circuit protection is provided by a precise               |
|-----------------------|---|
|                       | magnetic coil   |
|                       | Advanced contact design and arcing chambers pro-                |
|                       | vide the latest in fault current protection                     |
| Application           |   |
|                       | For molecular quitable configurations                           |
|                       | For molded case switch applications                             |
|                       | Can be installed in either the horizontal or vertical<br>planes |
|                       | Suitable for reverse feed applications                          |
| General               |   |
| Тгір Туре             | Magnetic only (MCS)   |
| Number of Poles       | 3   |
| Series                | TS3   |
| Approvals             |   |
| UL Class              | UL 489  |
| Dimension Information |   |
| H x W x D (inches)    | 6.7 x 4.13 x 4.07   |
| Specifications        |   |
| Rated Current (Amps)  | 225   |
| Rated Voltage AC      | 600   |
| Interrupt Rating      | 50kA at 480V AC   |
| Packaging             |   |
| Package in Units      | 1   |
| T&B Sold in UOM       | Each  |
| T&B Weight Per UOM    | 6.54 lbs. Each  |
|                       |   |