

# Product datasheet

Specifications



## serial link tap isolation box - for PLC Twido - screw terminal block - 2 RJ45

TWDXCAISO

### Main

Range of product	Twido
Accessory / separate part category	Connection accessories
accessory / separate part type	Tap isolation box
Accessory / separate part designation	Tap isolation box
Accessory / separate part destination	RS485 serial link
Product specific application	Lines prepolarised (2 R 620 Ohm) RS485 line isolation Line end adaptor (RC 120 Ohm, 1 nF)

### Complementary

Range compatibility	Twido programmable controller Modicon M238 logic controller
[Us] rated supply voltage	24 V
Supply circuit type	DC
Supply	External
Electrical connection	1 screw terminal block 2 connectors RJ45 (for tap-off)
Mounting support	35 mm symmetrical DIN rail
Net weight	0.1 kg

### Packing Units

Unit Type of Package 1	PCE
Number of Units in Package 1	1
Package 1 Height	6.6 cm
Package 1 Width	6.5 cm
Package 1 Length	12.0 cm
Package 1 Weight	156.0 g
Unit Type of Package 2	S02
Number of Units in Package 2	24
Package 2 Height	15 cm
Package 2 Width	30 cm
Package 2 Length	40 cm
Package 2 Weight	4.191 kg

Price is "List Price" and may be subject to a trade discount – check with your local distributor or retailer for actual price.

Disclaimer: This documentation is not intended as a substitute for and is not to be used for determining suitability or reliability of these products for specific user applications

Unit Type of Package 3	P12
Number of Units in Package 3	768
Package 3 Height	75 cm
Package 3 Width	120 cm
Package 3 Length	80 cm
Package 3 Weight	150 kg

## Contractual warranty

Warranty	18 months
----------	-----------