

# UA..RA 3-pole Contactors for Capacitor Switching

Peak Current  $\hat{I} \geq 100$  Times the rms Current



UA 16-30-10 RA



UA 30-30-10 RA



UA 75-30-00 RA

## Ordering Details

| Power                  | Auxiliary contacts fitted | Type                                                         | Order code                                                                             | Weight kg                      |
|------------------------|---------------------------|--------------------------------------------------------------|----------------------------------------------------------------------------------------|--------------------------------|
| 400 V<br>40 °C<br>kvar |                           | state coil voltage <input type="text"/><br>(see table below) | state coil voltage code <input type="text"/> <input type="text"/><br>(see table below) | Pack <sup>ing</sup><br>1 piece |
| 12.5                   | 1 –                       | UA 16-30-10 RA <input type="text"/>                          | 1SBL 181 024 R <input type="text"/> <input type="text"/> 10                            | 0.460                          |
| 22                     | 1 –                       | UA 26-30-10 RA <input type="text"/>                          | 1SBL 241 024 R <input type="text"/> <input type="text"/> 10                            | 0.710                          |
| 30                     | 1 –                       | UA 30-30-10 RA <input type="text"/>                          | 1SBL 281 024 R <input type="text"/> <input type="text"/> 10                            | 0.810                          |
| 40                     | – –                       | UA 50-30-00 RA <input type="text"/>                          | 1SBL 351 024 R <input type="text"/> <input type="text"/> 00                            | 1.350                          |
| 50                     | – –                       | UA 63-30-00 RA <input type="text"/>                          | 1SBL 371 024 R <input type="text"/> <input type="text"/> 00                            | 1.350                          |
| 60                     | – –                       | UA 75-30-00 RA <input type="text"/>                          | 1SBL 411 024 R <input type="text"/> <input type="text"/> 00                            | 1.350                          |

### Coil voltages and codes

| Voltage<br><input type="text"/> <input type="text"/> V - 50Hz | Voltage<br><input type="text"/> <input type="text"/> V - 60Hz | Code<br><input type="text"/> <input type="text"/> |
|---------------------------------------------------------------|---------------------------------------------------------------|---------------------------------------------------|
| 24                                                            | 24                                                            | 8 1                                               |
| 48                                                            | 48                                                            | 8 3                                               |
| 110                                                           | 110 ... 120                                                   | 8 4                                               |
| 220 ... 230                                                   | 230 ... 240                                                   | 8 0                                               |
| 230 ... 240                                                   | 240 ... 260                                                   | 8 8                                               |
| 380 ... 400                                                   | 400 ... 415                                                   | 8 5                                               |
| 400 ... 415                                                   | 415 ... 440                                                   | 8 6                                               |

Other voltages, consult page 0/1 of the main catalogue.