

UA..RA 3-pole Contactors for Capacitor Switching

Peak Current $\hat{I} \geq 100$ Times the rms Current



Ordering Details

Power	Auxiliary contacts fitted	Type	Order code	Weight kg
400 V 40 °C kvar		state coil voltage (see table below)	state coil voltage code (see table below)	Pack ^{ing} 1 piece
12.5	1 –	UA 16-30-10 RA	1SBL 181 024 R 10	0.460
22	1 –	UA 26-30-10 RA	1SBL 241 024 R 10	0.710
30	1 –	UA 30-30-10 RA	1SBL 281 024 R 10	0.810
40	– –	UA 50-30-00 RA	1SBL 351 024 R 00	1.350
50	– –	UA 63-30-00 RA	1SBL 371 024 R 00	1.350
60	– –	UA 75-30-00 RA	1SBL 411 024 R 00	1.350

Coil voltages and codes

Voltage V - 50Hz	Voltage V - 60Hz	Code
24	24	8 1
48	48	8 3
110	110 ... 120	8 4
220 ... 230	230 ... 240	8 0
230 ... 240	240 ... 260	8 8
380 ... 400	400 ... 415	8 5
400 ... 415	415 ... 440	8 6

Other voltages, consult page 0/1 of the main catalogue.



UA 16-30-10 RA



UA 30-30-10 RA



UA 75-30-00 RA