




Coils



LB4AN

Alternating current

CL...A	For use with	Cat. no. ⁽¹⁾	Weight
	CL00...CL25	LB1A ♦	0.063
	CL03...CL45	LB3A ♦	0.102
	CL05...CL10	LB4A ♦	0.145

Alternating current (V)

♦	C	D	F	G	H	J	K	M	N	R	S	T	U	V	W	X	Y	Z
50Hz		24	42	48		110			220	240			380		415	440	500	660
									230				400				690	

(1) To complete the catalogue number, replace the symbol ♦ by the corresponding code.

Direct current ⁽²⁾

CL...D	For use with	Cat. no. ⁽¹⁾	Weight
	CL00...CL25	LB1D ♦	0.205
	CL03...CL45	LB3D ♦	0.276

u	B	D	F	G	H	I	J	K	N	P	R	X
Voltage	12	12	24	42	48			110		220		240

(1) To complete the catalogue number, replace the symbol ♦ by the corresponding code.

Direct current (V) with electronic module (also for use with alternating current) ⁽²⁾

CL...E	For use with	Cat. no. ⁽¹⁾	Weight
	CL05...CL10	LB4E ♦	0.610

♦	D	F	H	J	N	Y
Voltage	24	42	60		220	440
	28	48		125	250	

(1) To complete the catalogue number, replace the symbol ♦ by the corresponding code.

(2) Operating limits 0.80 up to 1.10 x Us.

Contact kits

For use with	Number of sets ⁽¹⁾	Type	Cat. no.	Pack	Weight
CL00...	3	NO	V31200B	1	0.025
CL01...3..., CL01...4...	3	NO	V31201B	1	0.025
CL01...B	4	2NO-2NC	VB1201B	1	0.035
CL02...3, CL02...4...	3	NO	V31202B	1	0.025
CL02...B...	4	2NO-2NC	VB1202B	1	0.035
CL25...3...	3	NO	V31225B	1	0.035
CL03..., CL03...4...	3	NO	V31203B	1	0.035
CL03...B...	4	2NO-2NC	VB1203B	1	0.050
CL04...3..., CL04...4...	3	NO	V31204B	1	0.035
CL04...B	4	2NO-2NC	VB1204B	1	0.050
CL45...3...	3	NO	V31245B	1	0.035
CL05...4...	4	NO	V31205B	1	0.080
CL05...B...	4	2NO-2NC	VB1205B	1	0.100
CL06...	3	NO	V31206B	1	0.080
CL07...3..., CL07...4...	3	NO	V31207B	1	0.090
CL07...B...	4	2NO-2NC	VB1207B	1	0.110
CL08...3...	3	NO	V31208B	1	0.090
CL08...B...	4	2NO-2NC	VB1208B	1	0.110
CL09...	3	NO	V31209B	1	0.120
CL10...	3	NO	V31210B	1	0.130

(1) One set consists of two fixed contacts, one moving contact and accessory parts.