

# VBDN12

Switch disconnecter, TeSys Control, for ON/OFF, 12A(VN12),  $\bar{A}$ ~22.5 fixing, for mounting for mounting on door



## Main

Range	TeSys
Product name	TeSys Mini-VARIO
Device short name	VBDN
Product or component type	Switch disconnecter
Performance level	Standard
Poles description	3P
Contacts type and composition	3 NO
Network type	AC DC
Control type	Rotary handle
Rotary handle mounting style	Direct
Handle colour	Black
Handle front plate colour	Black
Rotary handle padlocking	1 to 3 padlocks 4...8 mm

## Complementary

Marking	0 - 1
Mounting support	Handle: door Switch: door
Fixing mode	Hole with 22.5 mm for handle
[Ue] rated operational voltage	690 V AC 50/60 Hz
[Uimp] rated impulse withstand voltage	6 kV
[Ith] conventional free air thermal current	12 A
[Ithe] conventional enclosed thermal current	10 A
[Ie] rated operational current	8.1 A (AC-23) at 400 V
Rated operational power in W	3 KW at 230...240 V (AC-23A) 4 KW at 400...415 V (AC-23A) 5.5 KW at 500 V (AC-23A) 7.5 KW at 690 V (AC-23A) 1.5 KW at 230...240 V (AC-3) 3 KW at 400...415 V (AC-3) 4 KW at 500 V (AC-3) 4 kW at 690 V (AC-3)
Intermittent duty class	30
Making capacity ( I Rms)	120 A at 400 V AC-21A 120 A at 400 V AC-22A 120 A at 400 V AC-23A
[Icm] rated short-circuit making capacity	0.5 kA at 400 V at Ipeak
[Icw] rated short-time withstand Rms current	140 A at 400 V duration: 1 s
Rated conditional short-circuit current	6 KA at 400 V - associated fuse 12 A aM 6 kA at 400 V - associated fuse 12 A gG
Breaking capacity	120 KA at 400 V (AC-21A) 120 KA at 400 V (AC-22A) 120 kA at 400 V (AC-23A)

Device composition	Switch Handle
Mechanical durability	50000 cycles
Electrical durability	30000 Cycles DC-1...5 50000 cycles AC-21
Suitability for isolation	Yes
Connections - terminals	Power circuit: screw clamp terminals4 mm² - flexible - with cable end Power circuit: screw clamp terminals4 mm² - solid
Tightening torque	Power circuit: 0.7 N.m - on screw clamp terminals
Handle front plate dimension	60 x 60 mm
Height	60 mm
Width	60 mm
Net weight	0.177 kg





## Environment

Standards	IEC 60947-3
Product certifications	UL[RETURN]GL[RETURN]CCC[RETURN]CSA[RETURN]UKCA
Protective treatment	TC
IP degree of protection	IP65
Mechanical robustness	Vibrations 10...150 Hz (5 gn) conforming to IEC 60068-2-6 Shocks 11 ms (15 gn) conforming to IEC 60068-2-27
Ambient air temperature for operation	-20...50 °C
Fire resistance	960 °C conforming to IEC 60695-2-1

## Packing Units

Unit Type of Package 1	PCE
Number of Units in Package 1	1
Package 1 Height	8.0 cm
Package 1 Width	8.5 cm
Package 1 Length	12.0 cm
Package 1 Weight	178.0 g
Unit Type of Package 2	S03
Number of Units in Package 2	24
Package 2 Height	30.0 cm
Package 2 Width	30.0 cm
Package 2 Length	40.0 cm
Package 2 Weight	4.776 kg

## Offer Sustainability

Sustainable offer status	Green Premium product
REACH Regulation	 <a href="#">REACH Declaration</a>
EU RoHS Directive	Compliant with Exemptions
Mercury free	Yes
China RoHS Regulation	 <a href="#">China RoHS Declaration</a>
RoHS exemption information	 Yes
Environmental Disclosure	 <a href="#">Product Environmental Profile</a>
Circularity Profile	No need of specific recycling operations
WEEE	The product must be disposed on European Union markets following specific waste collection and never end up in rubbish bins
PVC free	Yes
California proposition 65	WARNING: This product can expose you to chemicals including: Antimony oxide & Antimony trioxide, which is known to the State of California to cause cancer. For more information go to <a href="http://www.P65Warnings.ca.gov">www.P65Warnings.ca.gov</a>

## Contractual warranty

Warranty	18 months
----------	-----------