


Product data sheet

Specifications



Disconnect switch, TeSys VLS, CC fuse holder, for 3 pole disconnect switch, for up to 25A fuse

VLSFH1UL

Product availability: Stock - Normally stocked in distribution facility

Price*: 42.38 USD

Main

Range	TeSys
Product Name	TeSys VARIO LS
Device Short Name	VLSFH
Fuse Size	CC
Product Or Component Type	Fuse holder
Poles Description	3P
Network Type	AC

Complementary

Network Frequency	50/60 Hz
Mounting Support	DIN rail
[Uij] Rated Insulation Voltage	690 V AC 50/60 Hz
[Ith] Conventional Free Air Thermal Current	25 A 131 °F (55 °C)
Connections - Terminals	Power circuit screw clamp terminals 0.02 in² (10 mm²) solid Power circuit screw clamp terminals 0.02 in² (16 mm²) flexible without cable end
Tightening Torque	Power circuit 15.93...17.70 lbf.in (1.8...2 N.m) screw clamp terminals
Height	2.96 in (75.2 mm)
Width	2.07 in (52.5 mm)
Depth	3.15 in (80.1 mm)
Net Weight	0.30 lb(US) (0.135 kg)

Environment

Standards	UL 508 CSA C22.2 No 14 IEC 60947-3
Product Certifications	cULus GL
Ip Degree Of Protection	IP20 IEC 60529
Ambient Air Temperature For Operation	-13...131 °F (-25...55 °C)

Ordering and shipping details

Category	US10CP121734
----------	--------------

Price is "List Price" and may be subject to a trade discount – check with your local distributor or retailer for actual price.

Disclaimer: This documentation is not intended as a substitute for and is not to be used for determining suitability or reliability of these products for specific user applications

Discount Schedule	0CP1
Gtin	3606481157140
Returnability	Yes
Country Of Origin	IT

Packing Units

Unit Type Of Package 1	PCE
Number Of Units In Package 1	1
Package 1 Height	2.56 in (6.5 cm)
Package 1 Width	3.54 in (9.0 cm)
Package 1 Length	3.82 in (9.7 cm)
Package 1 Weight	4.76 oz (135.0 g)
Unit Type Of Package 2	S02
Number Of Units In Package 2	18
Package 2 Height	5.91 in (15.0 cm)
Package 2 Width	11.81 in (30.0 cm)
Package 2 Length	15.75 in (40.0 cm)
Package 2 Weight	6.05 lb(US) (2.746 kg)

Sustainability





Green Premium™ label is Schneider Electric’s commitment to delivering products with best-in-class environmental performance. Green Premium promises compliance with the latest regulations, transparency on environmental impacts, as well as circular and low-CO₂ products.

Guide to assessing product sustainability is a white paper that clarifies global eco-label standards and how to interpret environmental declarations.

[Learn more about Green Premium >](#)

[Guide to assess a product’s sustainability >](#)

Well-being performance

	Reach Free Of Svhc	
	Toxic Heavy Metal Free	
	Mercury Free	
	Rohs Exemption Information	Yes
Reach Regulation	REACH Declaration	
Eu Rohs Directive	Compliant EU RoHS Declaration	
China Rohs Regulation	China RoHS declaration Pro-active China RoHS declaration (out of China RoHS legal scope)	