


Kinetix VPF Food-grade Servo Motors

VPF-B1001M-PJ12AF



Representative Rendering, Not The Actual Product

VPF Food Grade Servo Motors, (B) 480V AC, (100) 100mm Bolt Circle Frame Size, (1) One Magnet Stack, (M) Winding, 6700 RPM Rated Speed, (P) 18 bit Single-turn and 12 bit Multi-turn Digital High Resolution Encoder, (J) Keyed Shaft, (1) Single SpeedTec Din Connector, (2) No Holding Brake, , (F) Food Grade Shaft Seal

Product Details

PRODUCT SELECTION	
Bulletin Number	VPF Food Grade Servo Motors
Voltage Class	(B) 480V AC
Frame Size	(100) 100mm Bolt Circle Frame Size
Stack Length	(1) One Magnet Stack
Rated Speed	(M) Winding, 6700 RPM Rated Speed
Feedback	(P) 18 bit Single-turn and 12 bit Multi-turn Digital High Resolution Encoder
Shaft Extension	(J) Keyed Shaft
Connectors	(1) Single SpeedTec Din Connector
Brake Option	(2) No Holding Brake
Mounting	(A) IEC Metric Mounting Flange
Factory Options	(F) Food Grade Shaft Seal
Torque Rating	Torque Rating

Supporting Documentation and Downloads

- [Product Profile \(Web page\)](#)
- [Motion Control Selection Guide \(Web page\)](#)
- [Rotary Motion Specifications Technical Data](#)
- [Motion Accessories Specifications Technical Data](#)
- [Photo](#)