

Product data sheet

Specifications



ferrite suppressors for downstream contactor opening

VW3A31453

Product availability: Non-Stock - Not normally stocked in distribution facility

Price*: 81.00 USD

Main

Product or Component Type	Ferrite suppressors for downstream contactor opening
Range Compatibility	Altivar 312 Altivar 312 Solar Altivar 12
Product Specific Application	Output filter
compatibility with variable speed drives	Variable speed drive ATV12H 0.55 kW, 200...240 V, single phase Variable speed drive ATV12H 0.75 kW, 200...240 V, single phase Variable speed drive ATV12H 1.5 kW, 200...240 V, single phase Variable speed drive ATV12H 2.2 kW, 200...240 V, single phase Variable speed drive ATV12H 0.75 kW, 200...240 V, three phase Variable speed drive ATV12H 1.5 kW, 200...240 V, three phase Variable speed drive ATV12H 2.2 kW, 200...240 V, three phase Variable speed drive ATV312 0.55 kW, 200...240 V, single phase Variable speed drive ATV312 0.75 kW, 200...240 V, single phase Variable speed drive ATV312 1.1 kW, 200...240 V, single phase Variable speed drive ATV312 1.5 kW, 200...240 V, single phase Variable speed drive ATV312 2.2 kW, 200...240 V, single phase Variable speed drive ATV312 0.55 kW, 200...240 V, three phase Variable speed drive ATV312 0.75 kW, 200...240 V, three phase Variable speed drive ATV312 1.1 kW, 200...240 V, three phase Variable speed drive ATV312 1.5 kW, 200...240 V, three phase Variable speed drive ATV312 2.2 kW, 200...240 V, three phase
Sale per indivisible quantity	3

Ordering and shipping details

Category	US1CP4B22042
Discount Schedule	CP4B
GTIN	3389110698954
Returnability	No
Country of origin	FR

Packing Units

Unit Type of Package 1	PCE
Number of Units in Package 1	1
Package 1 Height	4.134 in (10.500 cm)
Package 1 Width	6.299 in (16.000 cm)
Package 1 Length	5.512 in (14.000 cm)
Package 1 Weight	5.432 oz (154.000 g)
Unit Type of Package 2	S03
Number of Units in Package 2	7

Price is "List Price" and may be subject to a trade discount – check with your local distributor or retailer for actual price.

Disclaimer: This documentation is not intended as a substitute for and is not to be used for determining suitability or reliability of these products for specific user applications

Package 2 Height	11.811 in (30.000 cm)
Package 2 Width	11.811 in (30.000 cm)
Package 2 Length	15.748 in (40.000 cm)
Package 2 Weight	3.263 lb(US) (1.480 kg)
Unit Type of Package 3	P06
Number of Units in Package 3	56
Package 3 Height	29.528 in (75.000 cm)
Package 3 Width	23.622 in (60.000 cm)
Package 3 Length	31.496 in (80.000 cm)
Package 3 Weight	48.158 lb(US) (21.844 kg)

Contractual warranty

Warranty	18 months
----------	-----------

Sustainability




Green Premium™ label is Schneider Electric's commitment to delivering products with best-in-class environmental performance. Green Premium promises compliance with the latest regulations, transparency on environmental impacts, as well as circular and low-CO₂ products.

Guide to assessing product sustainability is a white paper that clarifies global eco-label standards and how to interpret environmental declarations.

[Learn more about Green Premium >](#)

[Guide to assess a product's sustainability >](#)

Well-being performance

 Reach Free Of Svhc	
 Mercury Free	
 Rohs Exemption Information	Yes
Reach Regulation	REACH Declaration
Eu Rohs Directive	Pro-active compliance (Product out of EU RoHS legal scope)
China Rohs Regulation	China RoHS declaration
California Proposition 65	WARNING: This product can expose you to chemicals including: Lead and lead compounds, which is known to the State of California to cause cancer and birth defects or other reproductive harm. For more information go to www.P65Warnings.ca.gov